


23252 KMC-25-40

Modular contactor, 230 VAC control voltage

5905339232526



Contactor is used for automatic activation of electricity receivers. Categories of use AC7a, AC7b.

PRODUCT PARAMETERS:

Utilisation category: AC-7A, AC-7B

Colour: white

Place of assembly: rail TH35

Place of application: Indoors

Norm: PN-EN 60947-4-1

Rated voltage [V]: 230 AC

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Connection type: Terminal block

Number of n.o./n.c. contacts: 4/0

Number of modules: 2

Rated power AC-7A/400: 15kW

Rated power AC-7B/400: 4kW

Coil-supply voltage [V]: 230V AC 50/60Hz

Rated current I(N) AC-7A/AC-1: 25A

Rated current I(N) AC-7B/AC-1: 8,5A

IP class: 20

LOGISTIC DATA:

Packaging method: 6

Number of units in the secondary packaging: 6

Number of units in the packaging: 60

Net unit weight [g]: 206

Grammage [g]: 223.33

Length of a unit pack [cm]: 3.5

Width of a unit pack [cm]: 7

Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 13.3998

Width of a cardboard box [cm]: 24.5

Height of a cardboard box [cm]: 20

Length of a cardboard box [cm]: 46

Volume of a cardboard box [m³]: 0.02254

IDEAL^{TS}

by **Kanlux**

ul. Objazdowa 1-3, 41-922 Radzionków, Poland

23252 KMC-25-40

Modular contactor, 230 VAC control voltage

Date of issue: 15.11.2022, 11:11

We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.

EN