

IMBFR I FD NW 23520


LED mirror light fitting 5905339235206













Kanlux IMBER LED is a waterproof holder intended for building in. Low temperature of work is one of its assets, thanks to which it can be easily mounted in wood as well. The unique structure of the holder means a regular emission of light and LED diodes used here guarantee high energy efficiency. The Kanlux IMBER LED holder is a perfect idea to highlight shower baths or outdoor soffits outside a house.

PRODUCT PARAMETERS:

Colour: aluminium

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,1m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-

insulating material: yes **Height [mm]**: 16.3 Diameter [mm]: 30

Assembly hole [mm]: Ø27

Integrated LED light source: yes Rated voltage [V]: 12 AC; 12 DC

Maximum power [W]: 1

Class of protection against electric shock: III

Lampshade material: plastic

Diode type: LED SMD Luminous flux [lm]: 40 Colour temperature: white Service life [h]: 30000

Number of on/off cycles: ≥20000

Lighting angle [°]: 105

Ambient temperature range to which the product can be

exposed: -20÷50


Enclosure material: aluminum alloy Connection type: Free cable ends Lamp-heating time [s]: ≤ 1 Lamp-ignition time [s]: ≤ 0.5

IP class: 65

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80







IMBER LED NW 23520

LED mirror light fitting



LOGISTIC DATA:


Packaging method: 200

Number of units in the secondary packaging: 1

Number of units in the packaging: 200 Number of units per layer on a pallet: 1400

Net unit weight [g]: 14 **Grammage [g]**: 38.5

Length of a unit pack [cm]: 2 Width of a unit pack [cm]: 9 Height of a unit pack [cm]: 12 Weight of a cardboard box [kg]: 7.7 Width of a cardboard box [cm]: 46.5 Height of a cardboard box [cm]: 23 Length of a cardboard box [cm]: 47 Volume of a cardboard box [m³]: 0.050267



KANLUX S.A. (kat 23520) IMBER LED NW / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 23520) IMBER LED NW Lampy: 1 x IMBER LED NW

