


23611 KDB-S08T

KDB-series distribution board

5905339236111



KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

PRODUCT PARAMETERS:

Colour: white / blue
Door colour: blue
Place of assembly: wall mounted
Norm: PN-EN 62208
Length [mm]: 225
Width [mm]: 102
Height [mm]: 204
Rated voltage [V]: 230/400 AC
Rated current [A]: 63
Rated frequency [Hz]: 50
Class of protection against electric shock: II
Material: plastic
Number of modules: 8P
Temperature resistance [°C]: 650
IK class: 07
IP class: 30
number of rows: 1

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 20
Number of units in the secondary packaging: 1
Number of units in the packaging: 20
Net unit weight [g]: 540
Grammage [g]: 758
Gross unit weight [g]: 672
Length of a unit pack [cm]: 21
Width of a unit pack [cm]: 10.5
Height of a unit pack [cm]: 23.5
Weight of a cardboard box [kg]: 15.16
Width of a cardboard box [cm]: 45
Height of a cardboard box [cm]: 49
Length of a cardboard box [cm]: 55.5

23611 KDB-S08T

KDB-series distribution board

| Volume of a cardboard box [m³] : 0.122378