


23612 KDB-S12T

KDB-series distribution board

5905339236128



KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

PRODUCT PARAMETERS:

Colour: white / blue

Door colour: blue

Place of assembly: wall mounted

Norm: PN-EN 62208

Length [mm]: 300

Width [mm]: 102

Height [mm]: 204

Rated voltage [V]: 230/400 AC

Rated current [A]: 63

Rated frequency [Hz]: 50

Class of protection against electric shock: II

Material: plastic

Number of modules: 12P

Temperature resistance [°C]: 650

IK class: 07

IP class: 30

number of rows: 1

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 10

Number of units in the secondary packaging: 1

Number of units in the packaging: 10

Net unit weight [g]: 770

Grammage [g]: 1062

Gross unit weight [g]: 930

Length of a unit pack [cm]: 21

Width of a unit pack [cm]: 11

Height of a unit pack [cm]: 31

Weight of a cardboard box [kg]: 10.62

Width of a cardboard box [cm]: 45

Height of a cardboard box [cm]: 33

Length of a cardboard box [cm]: 55

23612 KDB-S12T

KDB-series distribution board

| Volume of a cardboard box [m³] : 0.081675