


23620 KDB-F24T

KDB-series distribution board

5905339236203



KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

PRODUCT PARAMETERS:

Colour: white / blue

Door colour: blue

Place of assembly: Recessed mount in the wall

Norm: PN-EN 62208

Length [mm]: 317

Width [mm]: 109

Height [mm]: 310

Rated voltage [V]: 230/400 AC

Rated current [A]: 63

Rated frequency [Hz]: 50

Class of protection against electric shock: II

Material: plastic

Number of modules: 2x12P

Temperature resistance [°C]: 650

IK class: 07

IP class: 30

number of rows: 2

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 5

Number of units in the secondary packaging: 1

Number of units in the packaging: 5

Net unit weight [g]: 1230

Grammage [g]: 1658

Gross unit weight [g]: 1582

Length of a unit pack [cm]: 33

Width of a unit pack [cm]: 11.5

Height of a unit pack [cm]: 32

Weight of a cardboard box [kg]: 8.29

Width of a cardboard box [cm]: 33

Height of a cardboard box [cm]: 33

Length of a cardboard box [cm]: 59.5

23620 KDB-F24T

KDB-series distribution board

| **Volume of a cardboard box [m³]** : 0.064796