

Kanlux



EAN: 5905339237996

Staircase LED light fitting
Kanlux 23799 APUS LED PIR W-NW



Date of issue: 26.06.2026, 11:14

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

EN

PRODUCT PARAMETERS

Rated voltage [V]	12 DC
Maximum power [W]	0,8
Luminous flux [lm]	14
Correlated colour temperature [K]	4000
Colour consistency in McAdam ellipses	≤6
Colour temperature	white
Luminous efficiency of the lamp [lm/W]	18
Diode type	LED SMD
Integrated LED light source	yes
Colour rendering index	80
Service life [h]	50000
Number of on/off cycles	≥20000
To be built into the wall	yes
Place of application	Indoors
IP class	20
Compatible with a dimmer	no
Product category according to 2019/2020/EU	nie podlega pod rozporządzenie 2019/2020

DIMENSIONS AND MOUNTING

Height [mm]	75
Width [mm]	23
Length [mm]	75
Wire length [m]	0.18
Required diameter of the assembly box [Ømm]	60
Place of assembly	Recessed mount in the wall
Assembly-hole dimensions [mm]	60
Connection type	Free cable ends

LOGISTICS

Unit of measurement	unit
Packaging method	100
Number of units in the secondary packaging	1
Number of units in the packaging	100
Net unit weight [g]	84
Grammage [g]	102
Gross unit weight [g]	96
Length of a unit pack [cm]	11
Width of a unit pack [cm]	2.5
Height of a unit pack [cm]	16.5
Weight of a cardboard box [kg]	10.2
Width of a cardboard box [cm]	26
Height of a cardboard box [cm]	24
Length of a cardboard box [cm]	77
Volume of a cardboard box [m ³]	0.048048

SENSOR PARAMETERS

Sensor type	PIR
Motion detection	yes
Sensor range [m]	max 5
Sensor working angle [°]	H90/V40
Sensor-operation time [second-minute]	60--

MATERIAL AND CONSTRUCTION

Colour	white
Enclosure material	polished stainless steel, plastic
Lampshade material	plastic
Class of protection against electric shock	III
Kształt	square
Minimum distance from the illuminated object	0,1m
Ambient temperature range to which the product can be exposed	5÷25

Date of issue: 26.06.2026, 11:14

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com