


23920 KSD-T1T2 275/240 3P+N

Surge protector

5905339239204



Varistor surge arrester, class 1+2 (T1+T2/B+C): used to protect LV power installations against effects of surges occurring during lightning strikes and induced or switching surges / designed for installations in TN/TT grids. Compliance with standards: EN61643-1, EN61643-11. KSD-T1+T2 surge arresters (SPD) are made in accordance with EN61643-1, EN61643-11. These type 1+2 surge arresters are designed to protect low voltage installations against partial, direct and indirect atmospheric discharges. Arresters provide protection in the 0A-1 zone in accordance with EN62305 standard.

PRODUCT PARAMETERS:

Place of assembly: na szynę TH35

Place of application: Indoors

Norm: PN-EN61643-1

Width [mm]: 70

Height [mm]: 91

Depth [mm]: 68

Number of fields: 4

Rated voltage [V]: 230 AC

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -5÷40

Connection type: Terminal block

Protection type: T1+T2 (B+C)

Number of modules: 4

The highest voltage of continuous operation U(c): 275V

The highest discharge power I_{max} : 60kA

Voltage protection level $U(p)$: ≤1,5kV

Residual current $I(pe)$: 30µA

Impulse-current limp [kA]: 12

Transitory current-strength increase [kA]: 30

Expected short-circuit current I_{fi} [A] r.m.s. : 100

IP class: 20

Relative humidity range: 5÷95

Rated discharge current I_n [kA]: 30

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 3

Number of units in the secondary packaging : 3

Number of units in the packaging : 72

23920 KSD-T1T2 275/240 3P+N**Surge protector**

Net unit weight [g]:	570
Grammage [g]:	643.89
Length of a unit pack [cm]:	10.5
Width of a unit pack [cm]:	7.5
Height of a unit pack [cm]:	8
Weight of a cardboard box [kg]:	46.36008
Width of a cardboard box [cm]:	29
Height of a cardboard box [cm]:	26
Length of a cardboard box [cm]:	30.5
Volume of a cardboard box [m³]:	0.022997