

23924 KSD-T1+T2 275/60 M

Surge protector

5905339239242



PRODUCT PARAMETERS:

Place of assembly: na szynę TH35

Place of application: Indoors

Norm: PN-EN61643-1

Number of fields: 1

Rated voltage [V]: 230 AC

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -5÷40

Connection type: Terminal block

Protection type: T1+T2 (B+C)

Number of modules: 1

The highest voltage of continuous operation U(c): 275V

The highest discharge power I_{max}: 60kA

Voltage protection level U(p): ≤1,3kV

Residual current I(pe): 30μA

Impulse-current limp [kA]: 12.5

Transitory current-strength increase [kA]: 30

Expected short-circuit current Ifi [A] r.m.s. : 100

IP class: 20

Relative humidity range: 5÷95

Rated discharge current I_n [kA]: 30

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1

Number of units in the secondary packaging : 1

Number of units in the packaging : 1

Net unit weight [g]: 86

Grammage [g]: 106

Length of a unit pack [cm]: 10.5

Width of a unit pack [cm]: 2.5

Height of a unit pack [cm]: 7.5

Weight of a cardboard box [kg]: 0.106

Width of a cardboard box [cm]: 2.5

Height of a cardboard box [cm]: 7.5

Length of a cardboard box [cm] : 10.5

Volume of a cardboard box [m³]: 0.000197