


24107 KCP-25-24

KCP power contactor

5905339241078



Power contactors are designed to connect AC circuits in AC3 utilisation category. Current range of the offer up to 32A, supply voltage 24VAC or 230VAC. As a standard, contactors have a 1NO auxiliary contact.

PRODUCT PARAMETERS:

Utilisation category: AC-3

Colour: white

Place of assembly: rail TH35

Norm: PN-EN 60947-4-1

Rated frequency [Hz]: 50

Connection type: Terminal block

Electric connection frequency AC-3 [number/h]: 1200

Electric connection frequency AC-4 [number/h]: 300

Mechanical connection frequency [number/h]: 3600

Impedancja na biegun [mΩ]: 2

Rated operating power AC-3 220-240V: 5,5kW

Rated operating power AC-3 380-400V: 11kW

Rated operating power AC-3 415 V: 11kW

Rated operating power AC-3 440 V: 11kW

Rated operating power AC-3 660-690V: 15kW

Coil-supply voltage [V]: 24 AC

Rated breaking voltage U_e [V]: 400

Conventional thermal current I_{th} [A]: 40

Tightening force [Nm]: 2,5Nm

IP class: 20

Main contacts: 3

Auxiliary contacts: 1

Rated insulation voltage U_i [V]: 690

Rated impulse withstand voltage U_{imp} [V]: 6000

Rated operational current I_e [A]: 25

Rated operating current 380V - I_n AC-3: 25A

Rated operating current 380V - I_n AC-4: 8,5A

Rated operating current 440V - I_n AC-1: 40A

Rated operating current 660V - I_n AC-3: 18A

Rated operating current 660V - I_n AC-4: 4,4A

Żywotność elektryczna (x10³) AC-3: 1000

Żywotność elektryczna (x10³) AC-4: 200

Żywotność mechaniczna (x10⁶): 10Nm

24107 KCP-25-24

KCP power contactor

LOGISTIC DATA:

Packaging method: 50
Number of units in the secondary packaging: 1
Number of units in the packaging: 50
Net unit weight [g]: 514
Grammage [g]: 542
Length of a unit pack [cm]: 8.5
Width of a unit pack [cm]: 6
Height of a unit pack [cm]: 10.5
Weight of a cardboard box [kg]: 27.1
Width of a cardboard box [cm]: 32
Height of a cardboard box [cm]: 23
Length of a cardboard box [cm]: 45
Volume of a cardboard box [m³]: 0.03312

ACCESSORIES:

24110 KCP-AX11 Blok styków pomocniczych do styczników mocy - frontowe



24111 KCP-AX22 Blok styków pomocniczych do styczników mocy - frontowe

