

25338 BIURO 04-2010-102 bi

PIR motion sensor

5905339253385



PRODUCT PARAMETERS:

Colour: white

Place of assembly: slot 45x45

Place of application: Indoors

Micro-interval between relay contacts: yes

Length [mm]: 45

Width [mm]: 47

Height [mm]: 45

Sensitivity regulation: yes

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Class of protection against electric shock: II

Material: plastic

Sensor type: PIR

Connection type: Terminal block

sensor working angle [°]: 80

Number of modules: 2

Maximum load [W]: 400

Maximum operating time [min]: 10

Minimum operating time[s]: 5

Illumination-level setpoint by which the sensor detects movement [lx]: 1-2000

IP class: 20

Sensor range[m]: 3,5-9

LOGISTIC DATA:

Packaging method: 36

Number of units in the secondary packaging: 36

Number of units in the packaging: 360

Net unit weight [g]: 52

Grammage [g]: 57.78

Length of a unit pack [cm]: 4.5

Width of a unit pack [cm]: 4.5

Height of a unit pack [cm]: 4

Weight of a cardboard box [kg]: 20.8008

Width of a cardboard box [cm]: 28

Height of a cardboard box [cm]: 35



by **Kanlux**

ul. Objazdowa 1-3, 41-922 Radzionków, Poland



25338 BIURO 04-2010-102 bi

PIR motion sensor

Length of a cardboard box [cm] : 50

Volume of a cardboard box [m³]: 0.049