

26441 VARSO LED 18W-NW-O

Ceiling-mounted LED light fitting

5905339264411



Kanlux VARSO LED is a family of hermetic ceiling light fixtures with an integrated LED light source. It is a great choice both for developments (housing co-operatives, hotels) and individual households where increased resistance to humidity (IP54) is needed. For lighting particularly large spaces, we recommend 36W Kanlux VARSO HI with a luminous flux up to 3600 lm. Keep in mind that we also offer Kanlux VARSO fixtures with motion sensors (SE).

TYPE OF LIGHT SOURCE:


Lighting technology used: LED
Non-directional or directional light source: NDLS
Mains or non-mains light source: NMLS
Connected light source (CLS): no
Colour-tuneable light source: no
High luminance light source: no
Anti-glare shield: no
Dimmable: no

PRODUCT PARAMETERS:

Colour: white
Place of assembly: ceiling mounted
Place of application: Indoors and outdoors
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Height [mm]: 49
Diameter [mm]: 278
Mercury content: no
Integrated LED light source: yes
Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 18
Class of protection against electric shock: II
Lampshade material: plastic
Diode type: LED SMD
LED module: EBCL280C
Luminous flux of the light fitting [lm]: 1700
Colour temperature: white
Service life [h]: 20000
Luminous-flux-retention factor at the end of rated service life: L70B50
Number of on/off cycles: ≥20000
Lighting angle [°]: 120
Ambient temperature range to which the product can be


26441 VARSO LED 18W-NW-O

Ceiling-mounted LED light fitting

**exposed:** -20÷35**Enclosure material:** plastic**Connection type:** Self-clamping block**Range of sections of wires used [mm²]:** 0,5-2,5**Lamp-heating time [s]:** ≤1**Lamp-ignition time [s]:** ≤0,5**IP class:** 54**Additional information:** It is not possible to replace the LED light source**Additional information:** Any control panel or control equipment can only be replaced by qualified personnel (Kanlux service only)**PARAMETERS FOR LED AND OLED LIGHT SOURCES:****Energy consumption in on-mode of the light source (kWh/1000h):** 17**Energy efficiency class:** E**Useful luminous flux of the light source Φ_{use} [lm]:** 2200**Useful luminous flux of the light source Φ_{use} [lm]:** in sphere (360°)**Correlated colour temperature [K]:** 4000**Colour consistency in McAdam ellipses:** ≤6**On-mode power of the light source P_{on} [W]:** 16.5**Height of the light source [mm]:** 255**Width of the light source [mm]:** 255**Depth of the light source [mm]:** 1**Colour rendering index:** 80**Chromaticity coordinates (x):** 0.38**Chromaticity coordinates (y):** 0.38**R9 colour rendering index value:** 18**Survival factor:** 0,9**The lumen maintenance factor:** 0,95**LOGISTIC DATA:****Packaging method:** 20**Number of units in the secondary packaging:** 1**Number of units in the packaging:** 20**Net unit weight [g]:** 710**Grammage [g]:** 925.5**Length of a unit pack [cm]:** 28.5**Width of a unit pack [cm]:** 5.5**Height of a unit pack [cm]:** 28.5**Weight of a cardboard box [kg]:** 18.51**Width of a cardboard box [cm]:** 58**Height of a cardboard box [cm]:** 31**Length of a cardboard box [cm]:** 59**Volume of a cardboard box [m³]:** 0.106082

26441 VARSO LED 18W-NW-O

Ceiling-mounted LED light fitting



KANLUX S.A. (kat 26441) VARSO LED 18W-NW-O / LDC (Polar)

Luminaire: KANLUX S.A. (kat 26441) VARSO LED 18W-NW-O
Lamps: 1 x VARSO LED 18W-NW

