


26461 TAXI SMD L C/M-NW

Recessed light fitting

5905339264619



Kanlux TAXI SMD is a LED accent luminaire. It can be installed both indoors and outdoors (IP54). A perfect choice for decorative lighting of stairs and platforms.

PRODUCT PARAMETERS:

Colour: chrome matte

Place of assembly: Recessed mount in the wall

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,1m

Compatible with a dimmer: no

Length [mm]: 70

Width [mm]: 50

Height [mm]: 70

Integrated LED light source: yes

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 0.6

Class of protection against electric shock: I

Diode type: LED SMD

Luminous flux [lm]: 10

Colour temperature: white

Service life [h]: 20000

Number of on/off cycles: ≥ 10000

Ambient temperature range to which the product can be exposed: -20÷35

Enclosure material: Metal

Panel/frame material: stainless steel

Protective glass material: glass

Connection type: Free cable ends

Wire length [m]: 0.22

Wire diameter [mm²]: 0.75

Lamp-heating time [s]: ≤ 1

Lamp-ignition time [s]: $\leq 0,5$

IP class: 54

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: ≤ 6

Colour rendering index: 80

26461 TAXI SMD L C/M-NW

Recessed light fitting

**LOGISTIC DATA:**

Packaging method: 10

Number of units in the secondary packaging: 10

Number of units in the packaging: 40

Net unit weight [g]: 190

Grammage [g]: 239

Length of a unit pack [cm]: 8.5

Width of a unit pack [cm]: 8

Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 9.56

Width of a cardboard box [cm]: 20.5

Height of a cardboard box [cm]: 34

Length of a cardboard box [cm]: 44

Volume of a cardboard box [m³]: 0.030668

