


## 26463 TAXI SMD P C/M-NW

Recessed light fitting

5905339264633



Kanlux TAXI SMD is a LED accent luminaire. It can be installed both indoors and outdoors (IP54). A perfect choice for decorative lighting of stairs and platforms.

### PRODUCT PARAMETERS:

**Colour:** chrome matte

**Place of assembly:** Recessed mount in the wall

**Place of application:** Indoors and outdoors

**Minimum distance from the illuminated object:** 0,1m

**Compatible with a dimmer:** no

**Length [mm]:** 110

**Width [mm]:** 50

**Height [mm]:** 44

**Integrated LED light source:** yes

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** 0.6

**Class of protection against electric shock:** I

**Diode type:** LED SMD

**Luminous flux [lm]:** 10

**Colour temperature:** white

**Service life [h]:** 20000

**Number of on/off cycles:** ≥10000

**Ambient temperature range to which the product can be exposed:** -20÷35

**Enclosure material:** Metal

**Panel/frame material:** stainless steel

**Protective glass material:** glass

**Connection type:** Free cable ends

**Wire length [m]:** 0.22

**Wire diameter [mm<sup>2</sup>]:** 0.75

**Lamp-heating time [s]:** ≤1

**Lamp-ignition time [s]:** ≤0,5

**IP class:** 54

### PARAMETERS FOR LED AND OLED LIGHT SOURCES:

**Correlated colour temperature [K]:** 4000

**Colour consistency in McAdam ellipses:** ≤6

**Colour rendering index:** 80

## 26463 TAXI SMD P C/M-NW

Recessed light fitting

**LOGISTIC DATA:**

**Packaging method:** 10

**Number of units in the secondary packaging:** 10

**Number of units in the packaging:** 40

**Net unit weight [g]:** 204

**Grammage [g]:** 251.75

**Length of a unit pack [cm]:** 12.5

**Width of a unit pack [cm]:** 5.5

**Height of a unit pack [cm]:** 7

**Weight of a cardboard box [kg]:** 10.07

**Width of a cardboard box [cm]:** 29

**Height of a cardboard box [cm]:** 34

**Length of a cardboard box [cm]:** 31

**Volume of a cardboard box [m<sup>3</sup>]:** 0.030566

