


26687 ASTEN IP44 12W-NW-W

LED wall mounted fitting

5905339266873



Kanlux ASTEN LED is a linear wall luminaire to be used in places with increased humidity (IP44). You can easily mount it above the bathroom mirror. The lamp has a built-in light source based on SMD LED diodes, which lifetime is at least 25,000 hours.

TYPE OF LIGHT SOURCE:

Lighting technology used: LED

Non-directional or directional light source: NDLS

Mains or non-mains light source: NMLS

Connected light source (CLS): no

Colour-tuneable light source: no

High luminance light source: no

Anti-glare shield: no

Dimmable: no

PRODUCT PARAMETERS:

Colour: white

Place of assembly: wall mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,1m

Compatible with a dimmer: no

Fixture lighting direction: down

Length [mm]: 600

Width [mm]: 110

Height [mm]: 42

Mercury content: no

Integrated LED light source: yes

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 12

Class of protection against electric shock: II

Lampshade material: plastic

Diode type: LED SMD

Diode type: LED SMD

LED module: W600C40-66V-66-2835-SS

Luminous flux [lm]: 1070

Colour temperature: white

Service life [h]: 25000

Number of on/off cycles: ≥ 15000

Lighting angle [°]: X120/Y105

Ambient temperature range to which the product can be exposed: 5÷30

Enclosure material: aluminum alloy

Connection type: Bolt terminal block

26687 ASTEN IP44 12W-NW-W

LED wall mounted fitting

**Range of sections of wires used [mm²]:** 0,75÷1,5**Lamp-heating time [s]:** ≤1**Lamp-ignition time [s]:** ≤0,5**IP class:** 44**Additional information:** The LED light source can only be replaced by qualified personnel (Kanlux service only)**Additional information:** Any control panel or control equipment can only be replaced by qualified personnel (Kanlux service only)**PARAMETERS FOR LED AND OLED LIGHT SOURCES:****Energy consumption in on-mode of the light source (kWh/1000h):** 12**Energy efficiency class:** E**Useful luminous flux of the light source Φ_{use} [lm]:** 1450**Correlated colour temperature [K]:** 4000**Colour consistency in McAdam ellipses:** ≤6**On-mode power of the light source P_{on} [W]:** 11.2**Height of the light source [mm]:** 20**Width of the light source [mm]:** 595**Depth of the light source [mm]:** 1**Colour rendering index:** 80**Chromaticity coordinates (x):** 0,38**Chromaticity coordinates (y):** 0,38**R9 colour rendering index value:** 11**Survival factor:** 0,9**The lumen maintenance factor:** 0,95**PARAMETERS FOR LED AND OLED MAINS LIGHT SOURCES:****LED light source replaces a fluorescent light source without integrated ballast of a particular wattage:** Not applicable**LOGISTIC DATA:****Packaging method:** 20**Number of units in the secondary packaging:** 1**Number of units in the packaging:** 20**Net unit weight [g]:** 270**Grammage [g]:** 460.5**Length of a unit pack [cm]:** 13**Width of a unit pack [cm]:** 5**Height of a unit pack [cm]:** 61**Weight of a cardboard box [kg]:** 9.21**Width of a cardboard box [cm]:** 53**Height of a cardboard box [cm]:** 27.5**Length of a cardboard box [cm]:** 63**Volume of a cardboard box [m³]:** 0.091823

26687 ASTEN IP44 12W-NW-W

LED wall mounted fitting

KANLUX S.A. (kat 26687) ASTEN IP44 12W-NW-W / LDC (Polar)

Luminaire: KANLUX S.A. (kat 26687) ASTEN IP44 12W-NW-W
Lamps: 1 x ASTEN 12W

