


26820 SENTO

PIR motion sensor

5905339268204



Kanlux SENTO is an electronic sensor for movement detection. Its exceptionality lies in the fact that as many as three infrared detectors are installed in one sensor. This guarantees an unprecedented sensitivity and allows you to capture even the slightest movement. Kanlux SENTO, due to its unusual features, is referred to as a presence detector.

PRODUCT PARAMETERS:

Colour: white

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors

Micro-interval between relay contacts: yes

Length [mm]: 102

Width [mm]: 102

Height [mm]: 60

Sensitivity regulation: yes

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Class of protection against electric shock: II

Material: plastic

Ambient temperature range to which the product can be exposed: 5÷25

Sensor type: 3xPIR

Connection type: Terminal block

Range of sections of wires used [mm²]: 0,75÷1,5

Sensor-operation time [second-minute]: 10-30

sensor working angle [°]: H360/V120

Maximum operating time [min]: 30

Minimum operating time[s]: 10

Maximum power [VA]: 2000

Illumination-level setpoint by which the sensor detects movement [lx]: 3-2000

IP class: 20

Sensor range[m]: max 10

LOGISTIC DATA:

Packaging method: 50

Number of units in the secondary packaging: 1

Number of units in the packaging: 50

Net unit weight [g]: 142

Grammage [g]: 199.4

Length of a unit pack [cm]: 11

Width of a unit pack [cm]: 7

Height of a unit pack [cm]: 11

Weight of a cardboard box [kg]: 9.97

26820 SENTO

PIR motion sensor



Width of a cardboard box [cm]: 39
Height of a cardboard box [cm]: 24
Length of a cardboard box [cm]: 56
Volume of a cardboard box [m³]: 0.052416

