


## 27254 KMI-2/25A

Modular switch disconnecter

5905339272546



Switch disconnecter is used to disconnect circuits loaded with rated current.

### PRODUCT PARAMETERS:

**Utilisation category:** AC-22A

**Colour:** white

**Place of application:** Indoors

**Norm:** PN-EN 60947-3

**Length [mm]:** 76

**Width [mm]:** 35

**Height [mm]:** 82

**Rated voltage [V]:** 230/400 AC

**Rated current [A]:** 25

**Rated frequency [Hz]:** 50

**Ambient temperature range to which the product can be exposed:** -25÷45

**Range of sections of wires used [mm²]:** 1÷50

**Number of modules:** 2

**IP class:** 20

### LOGISTIC DATA:

**Packaging method:** 6

**Number of units in the secondary packaging:** 6

**Number of units in the packaging:** 60

**Net unit weight [g]:** 162

**Grammage [g]:** 180

**Length of a unit pack [cm]:** 3.5

**Width of a unit pack [cm]:** 7.5

**Height of a unit pack [cm]:** 8.5

**Weight of a cardboard box [kg]:** 10.8

**Width of a cardboard box [cm]:** 24.5

**Height of a cardboard box [cm]:** 20

**Length of a cardboard box [cm]:** 46

**Volume of a cardboard box [m³]:** 0.02254