

27804 ELNIS L W

Ring for spotlight fittings

5905339278043



The Kanlux ELNIS L is a fixture which consists of two parts forming a whole. It is a combination of two separate elements: the body (the main part) and the casing (the spacer ring), forming a perfectly matched whole. The ELNIS L is a fixture with a 25-mmhigh casing. The Kanlux ELNIS L is characterised by modern design and very-high quality of workmanship.

PRODUCT PARAMETERS:

Colour: white

Necessity of using self-shielding lamps: yes

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Decorative ring without a ceramic frame: yes

The product is not suitable to be covered with a heat-insulating material: yes

Light source included: no

Height [mm]: 44

Diameter [mm]: 98

Assembly hole [mm]: Ø70

Rated voltage [V]: 12 AC; 12 DC; 220-240 AC

Maximum power [W]: max 10

Class of protection against electric shock: II/III

Light source: MR16/PAR16

Cap: Gx5,3/GU10

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: aluminum alloy

Lighting-fixture angle regulation: none

IP class: 20

LOGISTIC DATA:

Packaging method: 50

Number of units in the secondary packaging: 1

Number of units in the packaging: 50

Net unit weight [g]: 160

Grammage [g]: 199.8

Length of a unit pack [cm]: 10

Width of a unit pack [cm]: 10

Height of a unit pack [cm]: 5

Weight of a cardboard box [kg]: 9.99

Width of a cardboard box [cm]: 21

Height of a cardboard box [cm]: 26.5

Length of a cardboard box [cm]: 52

Volume of a cardboard box [m³]: 0.028938

27804 ELNIS L W

Ring for spotlight fittings

ADDITIONAL INFORMATION:

- Decorative ring without a ceramic frame

