


28340 KDB-F54P

KDB-series distribution board

5905339283405



KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

PRODUCT PARAMETERS:

Colour: white

Door colour: white

Place of assembly: Recessed mount in the wall

Norm: PN-EN 62208

Length [mm]: 435

Width [mm]: 145

Height [mm]: 605

Rated voltage [V]: 230/400 AC

Rated current [A]: 63

Rated frequency [Hz]: 50

Class of protection against electric shock: II

Material: plastic

Number of modules: 3x18P

Temperature resistance [°C]: 650

IK class: 07

IP class: 30

number of rows: 3

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1

Number of units in the packaging: 1

Net unit weight [g]: 4430

Grammage [g]: 5910

Length of a unit pack [cm]: 63

Width of a unit pack [cm]: 47

Height of a unit pack [cm]: 18.5

Weight of a cardboard box [kg]: 5.91

Width of a cardboard box [cm]: 47

Height of a cardboard box [cm]: 18.5

Length of a cardboard box [cm]: 63

Volume of a cardboard box [m³]: 0.054779