

## 28341 KDB-F54P-M

KDB-series distribution board

5905339283412



KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

### PRODUCT PARAMETERS:

**Colour:** white

**Door colour:** white

**Place of assembly:** Recessed mount in the wall

**Norm:** PN-EN 62208

**Length [mm]:** 435

**Width [mm]:** 145

**Height [mm]:** 605

**Rated voltage [V]:** 230/400 AC

**Rated current [A]:** 63

**Rated frequency [Hz]:** 50

**Class of protection against electric shock:** II

**Material:** plastic

**Number of modules:** 18P

**Temperature resistance [°C]:** 650

**IK class:** 07

**IP class:** 30

**number of rows:** 1

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 1

**Number of units in the packaging:** 1

**Net unit weight [g]:** 4450

**Grammage [g]:** 5930

**Length of a unit pack [cm]:** 63

**Width of a unit pack [cm]:** 47

**Height of a unit pack [cm]:** 18.5

**Weight of a cardboard box [kg]:** 5.93

**Width of a cardboard box [cm]:** 47

**Height of a cardboard box [cm]:** 18.5

**Length of a cardboard box [cm]:** 63

**Volume of a cardboard box [m³]:** 0.054779

**28341 KDB-F54P-M**

KDB-series distribution board

