


28451 AL 4LED 120-MPR-SR

T8 LED tube linear fittings

5905339284518



PRODUCT PARAMETERS:

Colour: silver

Place of assembly: for suspension on the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Light source included: no

Fixture lighting direction: down

Power supply of T8 LED fluorescent lamps: Unilateral

Length [mm]: 1240

Width [mm]: 60

Height [mm]: 69

Wersja do łączenia w linie [element początkowy] LF: 33772 (Z)

Wersja do łączenia w linie [element środkowy] LM: 33778 (Z)

Wersja do łączenia w linie [element końcowy] LL: 33784 (Z)

Explanation of markings and signs used: (Z) - for suspension on the ceiling

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: max 36

Class of protection against electric shock: I

Lampshade material: plastic

Light source: T8 LED

Cap: G13

Ambient temperature range to which the product can be exposed: 5÷25

Shade type: microprismatic

Enclosure material: aluminum alloy

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 1,5÷2,5

IP class: 20

LOGISTIC DATA:

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 1800

Grammage [g]: 2134

Length of a unit pack [cm]: 136

Width of a unit pack [cm]: 11

Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 2.134

Width of a cardboard box [cm]: 11

Height of a cardboard box [cm]: 7

28451 AL 4LED 120-MPR-SR


T8 LED tube linear fittings



Length of a cardboard box [cm] : 136
Volume of a cardboard box [m³]: 0.010472


KANLUX S.A. (kat 28451) AL 4LED 120-MPR-SR + GLASSv4 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 28451) AL 4LED 120-MPR-SR + GLASSv4
Lamps: 1 x T8 LED GLASSv4 18W-NW



KANLUX S.A. (kat 28451) AL 4LED 120-MPR-SR + GLASSv3 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 28451) AL 4LED 120-MPR-SR + GLASSv3
Lamps: 1 x T8 LED GLASSv3 18W-NW




28451 AL 4LED 120-MPR-SR

T8 LED tube linear fittings

KANLUX S.A. (kat 28451) AL 4LED 120-MPR-SR + GLASSv2 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 28451) AL 4LED 120-MPR-SR + GLASSv2
Lamps: 1 x T8 LED GLASSv2 18W-WW



KANLUX S.A. (kat 28451) AL 4LED 120-MPR-SR + Miledo / LDC (Polar)

Luminaire: KANLUX S.A. (kat 28451) AL 4LED 120-MPR-SR + Miledo
Lamps: 1 x T8 LED 18W-WW

