


28640 FTD1200 37W-840-INT

LED dustproof lighting fitting

5905339286406



PRODUCT PARAMETERS:

Colour: grey

Place of assembly: ceiling mounted, wall mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Possibility of fixture-loop-through connection: yes

Compatible with a dimmer: DALI

Length [mm]: 1180

Width [mm]: 80

Height [mm]: 70

Integrated LED light source: yes

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 37

Class of protection against electric shock: I

Lampshade material: PC

Diode type: LED SMD

Luminous flux [lm]: 5200

Colour temperature: white

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life: L90B10

Number of on/off cycles: ≥ 30000

Lighting angle [°]: X70/Y95

Ambient temperature range to which the product can be exposed: $-25 \div 40$

Shade type: prismatic, narrow-beam

Enclosure material: PC

Connection type: Self-clamping block

Range of sections of wires used [mm²]: $0,5 \div 2,5$

Lamp-heating time [s]: ≤ 1

Lamp-ignition time [s]: $\leq 0,5$

Maximum number of loop-through-connected fixtures: 7

IK class: 08

IP class: 65

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: ≤ 3

Colour rendering index: 80

28640 FTD1200 37W-840-INT

LED dustproof lighting fitting

LOGISTIC DATA:**Packaging method:** 1**Number of units in the secondary packaging:** 1**Number of units in the packaging:** 1**Net unit weight [g]:** 2100**Grammage [g]:** 2280**Length of a unit pack [cm]:** 120**Width of a unit pack [cm]:** 8**Height of a unit pack [cm]:** 7**Weight of a cardboard box [kg]:** 2.28**Width of a cardboard box [cm]:** 9**Height of a cardboard box [cm]:** 7.5**Length of a cardboard box [cm] :** 120**Volume of a cardboard box [m³]:** 0.0081**ADDITIONAL INFORMATION:**

- 5 years Warranty under the terms of the warranty statement, available on our website

