

## 28863 FTD1500 43W-840-RYF

LED dustproof lighting fitting

5905339288639



**DALI**  
system



### PRODUCT PARAMETERS:

**Colour:** grey

**Place of assembly:** ceiling mounted, wall mounted

**Place of application:** Indoors and outdoors

**Minimum distance from the illuminated object:** 0,5m

**Possibility of fixture-loop-through connection:** yes

**Compatible with a dimmer:** DALI

**Length [mm]:** 1480

**Width [mm]:** 80

**Height [mm]:** 70

**Integrated LED light source:** yes

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** 43

**Class of protection against electric shock:** I

**Lampshade material:** PC

**Diode type:** LED SMD

**Luminous flux [lm]:** 6500

**Colour temperature:** white

**Service life [h]:** 50000

**Luminous-flux-retention factor at the end of rated service life:** L90B10

**Number of on/off cycles:** ≥30000

**Lighting angle [°]:** X115/Y105

**Ambient temperature range to which the product can be exposed:** -25÷40

**Shade type:** grooved

**Enclosure material:** PC

**Connection type:** Self-clamping block

**Range of sections of wires used [mm<sup>2</sup>]:** 0,5÷2,5

**Lamp-heating time [s]:** ≤1

**Lamp-ignition time [s]:** ≤0,5

**Maximum number of loop-through-connected fixtures:** 7

**IK class:** 08

**IP class:** 65

### PARAMETERS FOR LED AND OLED LIGHT SOURCES:

**Correlated colour temperature [K]:** 4000

**Colour consistency in McAdam ellipses:** ≤3

**Colour rendering index:** 80

**28863 FTD1500 43W-840-RYF**

LED dustproof lighting fitting

**LOGISTIC DATA:****Packaging method:** 1**Number of units in the secondary packaging:** 1**Number of units in the packaging:** 1**Net unit weight [g]:** 2660**Grammage [g]:** 2490**Length of a unit pack [cm]:** 150**Width of a unit pack [cm]:** 8**Height of a unit pack [cm]:** 7**Weight of a cardboard box [kg]:** 2.49**Width of a cardboard box [cm]:** 9**Height of a cardboard box [cm]:** 7.5**Length of a cardboard box [cm]:** 150**Volume of a cardboard box [m<sup>3</sup>]:** 0.010125**ADDITIONAL INFORMATION:**

- 5 years Warranty under the terms of the warranty statement, available on our website

