


28979 ONTEC G E1E180MATW

Emergency lighting LED

5902052563340



Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

PRODUCT PARAMETERS:

Colour: white
Place of assembly: ceiling mounted
Place of application: Indoors
Length [mm]: 250
Width [mm]: 29
Height [mm]: 194
Integrated LED light source: yes
Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Rated power [W]: 3
Rated power (LED) [W]: 0.9
Class of protection against electric shock: II
Lampshade material: plastic
Diode type: LED SMD
Colour temperature: cold white
Ambient temperature range to which the product can be exposed: 10÷35
Battery (type): LiFePO4/C
Battery (parameters): 3,2V 1,5Ah
Operating mode: emergency and network
Application: marking of escape routes
Fail-safe working time [h]: 3
Automatic test: yes
Enclosure material: plastic
Connection type: Self-clamping block
IP class: 20

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Correlated colour temperature [K]: 5000

LOGISTIC DATA:

Packaging method: 1
Number of units in the secondary packaging: 1
Number of units in the packaging: 1

28979 ONTEC G E1E180MATW

Emergency lighting LED

ACCESSORIES:

33813 ZEST MONT OG00 W

