


Kanlux

EAN: 5905339290724

Ceiling-mounted LED light fitting KANLUX 29072 PORTOS CCT M10W TSE



PRODUCT PARAMETERS

Rated voltage [V]

220-240 AC

Date of issue: 07.10.2026, 14:08

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

EN

PRODUCT PARAMETERS


Rated frequency [Hz]	50
Maximum power [W]	5 / 7 / 10
Luminous flux of the light fitting [lm]	max 500 (5W) / max 700 (7W) / max 1000 (10W)
Correlated colour temperature [K]	2700/3000/4000/5000/6500
Colour consistency in McAdam ellipses	6
Colour temperature	warm white, white, cold white
Power setting range [W]	5 / 7 / 10
Luminous flux setting range [lm]	max 500 (5W) / max 700 (7W) / max 1000 (10W)
Lighting angle [°]	110
Diode type	LED SMD
Integrated LED light source	yes
Colour rendering index	80
Service life [h]	25000
Number of on/off cycles	≥15000
Place of application	Indoors and outdoors
IP class	65
IK class	08
Compatible with a dimmer	no
LED light source replaceability	Possibility of replacing the LED light source only by qualified personnel (only by the manufacturer service)
Control gear replaceability	Possibility of replacing the control equipment only by qualified personnel (only by the manufacturer service)
Product category according to 2019/2020/EU	Containing product (CP)
Mercury content	no

DIMENSIONS AND MOUNTING

Height [mm]	52
Width [mm]	195
Length [mm]	300
Place of assembly	wall mounted
Connection type	Self-clamping block
Range of sections of wires used [mm²]	0,75÷1,5

LIGHT SOURCE PARAMETERS

Anti-glare shield	no
Dimmable	no



SENSOR PARAMETERS

Sensor type	dusk
Motion detection	no
Illumination-level setpoint by which the sensor detects movement [lx]	3/10/25/50

LIGHT SOURCE PARAMETERS

Energy efficiency class of the light source in the contains product (CP)	D
R9 colour rendering index value	0
Survival factor	0,9
The lumen maintenance factor	0,95
Colour-tuneable light source	no
High luminance light source	no

MATERIAL AND CONSTRUCTION

Colour	white
Enclosure material	plastic
Lampshade material	plastic
Class of protection against electric shock	II
Minimum distance from the illuminated object	0,5m
Ambient temperature range to which the product can be exposed	-15÷35

Date of issue: 07.10.2026, 14:08

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

LOGISTICS	
Unit of measurement	unit
Packaging method	10
Number of units in the secondary packaging	1
Number of units in the packaging	10
Net unit weight [g]	752
Grammage [g]	946.6
Gross unit weight [g]	868

LOGISTICS	
Length of a unit pack [cm]	30.5
Width of a unit pack [cm]	6.5
Height of a unit pack [cm]	21
Weight of a cardboard box [kg]	9.466
Width of a cardboard box [cm]	35.5
Height of a cardboard box [cm]	23.5
Length of a cardboard box [cm]	62.5
Volume of a cardboard box [m ³]	0.052141

Date of issue: 07.10.2026, 14:08

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com