


29112 MILENO EL-30 B-AG

Wall & ceiling lighting fitting

5905339291127



Kanlux MILENO follows the latest trends. The advantages of this series are its interesting design and original shape. The very-large number of Kanlux MILENO fixture models means many-more arrangement possibilities.

PRODUCT PARAMETERS:

Colour: black/gold

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Light source included: no

Height [mm]: 120

Diameter [mm]: 200

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 3 x max 10

Class of protection against electric shock: I

Light source: PAR16

Cap: GU10

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: steel

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 1÷2,5

The fixture is movable horizontally [°]: 300

The fixture is movable vertically [°]: 80

IP class: 20

LOGISTIC DATA:

Packaging method: 12

Number of units in the secondary packaging: 1

Number of units in the packaging: 12

Net unit weight [g]: 660

Grammage [g]: 923.33

Length of a unit pack [cm]: 24

Width of a unit pack [cm]: 13

Height of a unit pack [cm]: 24

Weight of a cardboard box [kg]: 11.07996

Width of a cardboard box [cm]: 41

Height of a cardboard box [cm]: 50

Length of a cardboard box [cm]: 49

Volume of a cardboard box [m³]: 0.10045

29112 MILENO EL-30 B-AG

Wall & ceiling lighting fitting

