


29127 LAURIN EL-30 B

Wall & ceiling lighting fitting

5905339291271



LAURIN EL-30 B



Kanlux LAURIN spotlights provide a very large selection of directional ceiling and wall lamps. The simple and minimalist design can be successfully used in many rooms in the house. Free adjustment of the luminous flux direction is an additional advantage of these fixtures.

PRODUCT PARAMETERS:

Colour: black

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Light source included: no

Height [mm]: 108

Diameter [mm]: 220

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 3 x max 10

Class of protection against electric shock: I

Lampshade material: aluminum alloy

Light source: PAR16

Cap (Light source): GU10

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: aluminum alloy

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 1÷2,5

The fixture is movable horizontally [°]: 310

The fixture is movable vertically [°]: 90

Lighting-fixture angle regulation [°]: in two axes

IP class: 20

Kształt: round

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 6

Number of units in the secondary packaging: 1

Number of units in the packaging: 6

Net unit weight [g]: 900

Grammage [g]: 1103.43

Gross unit weight [g]: 1050

Length of a unit pack [cm]: 22.5

Width of a unit pack [cm]: 11

29127 LAURIN EL-3O B

Wall & ceiling lighting fitting



Height of a unit pack [cm]: 22.5

Weight of a cardboard box [kg]: 6.62058

Width of a cardboard box [cm]: 35.5

Height of a cardboard box [cm]: 25

Length of a cardboard box [cm] : 46

Volume of a cardboard box [m³] : 0.040825