


31497 TOLU O LED 9W-NW-W

Bulkhead fixture

8595665314972



PRODUCT PARAMETERS

Rated voltage [V]	220-240 AC
Rated frequency [Hz]	50
Maximum power [W]	9
Luminous flux of the light fitting [lm]	720
Correlated colour temperature [K]	4000
Luminous efficiency of the lamp [lm/W]	80
Lighting angle [°]	120
Diode type	LED SMD
Integrated LED light source	yes
Colour consistency in McAdam ellipses	6
Colour temperature	white
Colour rendering index	80
Service life [h]	20000
Number of on/off cycles	≥15000
Place of application	Indoors and outdoors
IP class	54
Compatible with a dimmer	no

Date of issue: 24.03.2026, 08:49

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Aprisa s.r.o. Sadová 618, 738 01, Frýdek-Místek, Czech Republic aprisa@aprisa.cz

PRODUCT PARAMETERS

LED light source replaceability	It is not possible to replace the LED light source
Control gear replaceability	Possibility of replacing the control equipment only by qualified personnel (only by the manufacturer service)
Product category according to 2019/2020/EU	Containing product (CP)
Mercury content	no

DIMENSIONS AND MOUNTING

Height [mm]	38
Diameter [mm]	135
Place of assembly	wall mounted, ceiling mounted
Connection type	Self-clamping block
Range of sections of wires used [mm ²]	1-2,5

MATERIAL AND CONSTRUCTION

Colour	white
Enclosure material	plastic
Lampshade material	plastic
Class of protection against electric shock	II
Kształt	round
Minimum distance from the illuminated object	0,5m
Ambient temperature range to which the product can be exposed	-20÷40


LIGHT SOURCE PARAMETERS

Energy efficiency class of the light source in the contains product (CP)	F
Survival factor	0,9
The lumen maintenance factor	0,95
Colour-tuneable light source	no
High luminance light source	no
Anti-glare shield	no
Dimmable	no

LOGISTICS

Unit of measurement	unit
Packaging method	80
Number of units in the secondary packaging	1
Number of units in the packaging	80
Net unit weight [g]	92
Grammage [g]	113.75
Gross unit weight [g]	104
Length of a unit pack [cm]	13.5
Width of a unit pack [cm]	13.5
Height of a unit pack [cm]	4
Weight of a cardboard box [kg]	9.1
Width of a cardboard box [cm]	41
Height of a cardboard box [cm]	30
Length of a cardboard box [cm]	55.5
Volume of a cardboard box [m ³]	0.068265

PHOTOMETRIC DATA



Date of issue: 24.03.2026, 08:49

We reserve the right to make technical changes. The data contained in this material are not legally binding.


Photometry: the results obtained from testing were from a specific sample.

Aprisa s.r.o. Sadová 618, 738 01, Frýdek-Místek, Czech Republic aprisa@aprisa.cz

PHOTOMETRIC DATA

Miledo (kat 31497) TOLU O LED 9W-NW-W / Krzywa rozsyłu światła (biegunowo)

Oprawa: Miledo (kat 31497) TOLU O LED 9W-NW-W
Lampy: 1 x TOLU O LED 9W-NW-W



Date of issue: 24.03.2026, 08:49

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Aprisa s.r.o. Sadová 618, 738 01, Frýdek-Místek, Czech Republic aprisa@aprisa.cz

EN