

31530 AZPO LED 12,3WCCT-L-W

Ceiling-mounted LED light fitting

8595665315306

PRODUCT PARAMETERS:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 12.3

Luminous flux [lm]: 1150

Luminous efficiency of the lamp [lm/W]: 93

Lighting angle [°]: 120

Correlated colour temperature [K]: 3000/4000/6000

Colour consistency in McAdam ellipses: 6

Colour temperature: white, Warm white, cold white

Colour rendering index: 80

Service life [h]: 20000

Number of on/off cycles: ≥15000

Light source: LED

Diode type: LED SMD

Colour: white

Place of assembly: ceiling mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Length [mm]: 225

Width [mm]: 225

Height [mm]: 28

Integrated LED light source: yes

Class of protection against electric shock: II

Lampshade material: plastic

Enclosure material: plastic

Ambient temperature range to which the product can be exposed: -20÷40

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 0,75-1,5

IP class: 54

Kształt: square

LED light source replaceability: Possibility of replacing the LED light source only by qualified personnel (only by the manufacturer service)

Control gear replaceability: Possibility of replacing the control equipment only by qualified personnel (only by the manufacturer service)

Product category according to 2019/2020/EU: Containing product (CP)

Mercury content: no

31530 AZPO LED 12,3WCCT-L-W

Ceiling-mounted LED light fitting

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Energy efficiency class of the light source in the contains product (CP): E

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1