


**32821 OS 40W-840-MPRM-W-N3**

Surface-mounted LED office fixture

5905339328212

MO  
DE  
RN  
designEA  
SY  
instal  
lationMADE IN  
POLAND**PRODUCT PARAMETERS:****Colour:** white**Place of assembly:** ceiling mounted**Place of application:** Indoors**Minimum distance from the illuminated object:** 0,5m**Compatible with a dimmer:** no**The product is not suitable to be covered with a heat-insulating material:** yes**Length [mm]:** 1200**Width [mm]:** 300**Height [mm]:** 35**Integrated LED light source:** yes**Rated voltage [V]:** 220-240 AC**Rated frequency [Hz]:** 50**Maximum power [W]:** 40**Class of protection against electric shock:** I**Lampshade material:** plastic**Diode type:** LED SMD**Luminous flux [lm]:** 4400**Colour temperature:** white**Service life [h]:** 50000**Luminous-flux-retention factor at the end of rated service life:** L90B10**Number of on/off cycles:** ≥30000**Lighting angle [°]:** X90/Y95**Ambient temperature range to which the product can be exposed:** 5÷25**Shade type:** m-type microprismatic**Enclosure material:** Metal**Connection type:** Self-clamping block**Range of sections of wires used [mm²]:** 1,5÷2,5**Lamp-heating time [s]:** ≤1**Lamp-ignition time [s]:** ≤0,5**IP class:** 20**PARAMETERS FOR LED AND OLED LIGHT SOURCES:****Correlated colour temperature [K]:** 4000**Colour consistency in McAdam ellipses:** ≤3**Colour rendering index:** 80**LOGISTIC DATA:****Packaging method:** 1**Number of units in the secondary packaging:** 1**Number of units in the packaging:** 1**Net unit weight [g]:** 4150**Grammage [g]:** 4580

**32821 OS 40W-840-MPRM-W-N3**

Surface-mounted LED office fixture

**Length of a unit pack [cm]:** 123**Width of a unit pack [cm]:** 32.5**Height of a unit pack [cm]:** 5.5**Weight of a cardboard box [kg]:** 4.58**Width of a cardboard box [cm]:** 32.5**Height of a cardboard box [cm]:** 5.5**Length of a cardboard box [cm]:** 123**Volume of a cardboard box [m<sup>3</sup>]:** 0.021986**ADDITIONAL INFORMATION:**

- 5 years Warranty under the terms of the warranty statement, available on our website

KANLUX S.A. (kat 32821) OS 40W-840-MPRM-W-N3 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 32821) OS 40W-840-MPRM-W-N3

Lamps: 1 x OS 40W-840-MPRM-W-N3

