

32825 OS 40W-840-MPRM-B-N3

Surface-mounted LED office fixture


5905339328250



MO
DE
RN
design

EA
SY
instal
lation

MADE IN
POLAND



PRODUCT PARAMETERS:

Colour: black

Place of assembly: ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating material: yes

Length [mm]: 1200

Width [mm]: 300

Height [mm]: 35

Integrated LED light source: yes

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 40

Class of protection against electric shock: I

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 4300

Colour temperature: white

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life: L90B10

Number of on/off cycles: ≥30000

Lighting angle [°]: X90/Y95

Ambient temperature range to which the product can be exposed: 5÷25

Shade type: m-type microprismatic

Enclosure material: Metal

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 1,5÷2,5

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

IP class: 20

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: ≤3

Colour rendering index: 80

LOGISTIC DATA:

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 4190

Grammage [g]: 4620

Date of issue: 16.11.2022, 06:03

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

32825 OS 40W-840-MPRM-B-N3

Surface-mounted LED office fixture

Length of a unit pack [cm]: 123**Width of a unit pack [cm]:** 32.5**Height of a unit pack [cm]:** 5.5**Weight of a cardboard box [kg]:** 4.62**Width of a cardboard box [cm]:** 32.5**Height of a cardboard box [cm]:** 5.5**Length of a cardboard box [cm]:** 123**Volume of a cardboard box [m³]:** 0.021986**ADDITIONAL INFORMATION:**

- 5 years Warranty under the terms of the warranty statement, available on our website

KANLUX S.A. (kat 32825) OS 40W-840-MPRM-B-N3 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 32825) OS 40W-840-MPRM-B-N3

Lamps: 1 x OS 40W-840-MPRM-B-N3

