

## 33516 XLED A60 4W-SW

LED light source

5905339335166

1800K  
SUPER  
WARM



DE  
CO  
RI  
function



A decorative version of a "true LED bulb". Kanlux XLED in this exceptional version will help you create a very cosy atmosphere. All thanks to a very warm colour of the light and an amber glass in which a spiral LED filament is enclosed. This bulb will become a decoration of your house, café, restaurant and any other place in which you will install it. It is an exceptional combination of a decorative nature, vintage style and modern energy-efficient LED technology.

### TYPE OF LIGHT SOURCE:

**Lighting technology used:** LED

**Non-directional or directional light source:** NDLS

**Mains or non-mains light source:** MLS

**Colour-tunable light source:** no

**High luminance light source:** no

**Anti-glare shield:** no

**Dimmable:** no

### PRODUCT PARAMETERS:

**Colour:** amber

**Compatible with a dimmer:** no

**Height [mm]:** 108

**Diameter [mm]:** 60

**Mercury content:** no

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Lamp rated current [mA]:** 38

**Rated power [W]:** 4

**Total rated luminous flux [lm]:** 250

**Rated beam angle [°]:** 320

**Lampshade material:** glass

**Light source:** A60

**Diode type:** LED FILAMENT

**Colour temperature:** super warm

**Cap:** E27

**Rated lamp-service life [h]:** 15000

**Number of on/off cycles:** ≥20000

**Light source shape:** standard


### PARAMETERS FOR LED AND OLED LIGHT SOURCES:

**Energy consumption in on-mode of the light source**

**(kWh/1000h):** 4

**Useful luminous flux of the light source Φuse [lm]:** 250

**Useful luminous flux of the light source Φuse [lm]:** in



## 33516 XLED A60 4W-SW

### LED light source

sphere (360°)

**Correlated colour temperature [K]:** 1800

**Colour consistency in McAdam ellipses:** ≤6

**On-mode power of the light source Pon [W]:** 4

**Colour rendering index:** 80

**Claim of equivalent power [W]:** 25

#### PARAMETERS FOR LED AND OLED MAINS LIGHT SOURCES:

**Flicker metric (Pst LM):** ≤1,0

**Stroboscopic effect metric (SVM):** ≤0,9

#### LOGISTIC DATA:

**Packaging method:** 10

**Number of units in the secondary packaging:** 10

**Number of units in the packaging:** 100

**Net unit weight [g]:** 34

**Grammage [g]:** 62.3

**Length of a unit pack [cm]:** 6.5

**Width of a unit pack [cm]:** 6.5

**Height of a unit pack [cm]:** 12

**Weight of a cardboard box [kg]:** 6.23

**Width of a cardboard box [cm]:** 35

**Height of a cardboard box [cm]:** 27

**Length of a cardboard box [cm]:** 69.5

**Volume of a cardboard box [m³]:** 0.065678

KANLUX S.A. (kat 33516) XLED A60 4W-SW / LDC (Polar)

Luminaire: KANLUX S.A. (kat 33516) XLED A60 4W-SW  
Lamps: 1 x XLED A60 4W-SW

