Kanlux

ul. Objazdowa 1-3, 41-922 Radzionków, Poland

33518   XLED G95 4W-SW

LED light source

5905339335180

1800K SUPER WARM

320°

DECORI function

A decorative version of the GLOBE-type bulb. Kanlux XLED G95 will let you create a very cosy atmosphere. All thanks to a very warm colour of the light and an amber glass in which a spiral LED filament is enclosed. This ball of light will become a decoration of your house, café, restaurant and any other place in which you will install it. It is an exceptional combination of a decorative nature and a modern energy-efficient LED technology.

TYPE OF LIGHT SOURCE:

Lighting technology used: LED
Non-directional or directional light source: NDLS
Mains or non-mains light source: MLS
Colour-tuneable light source: no
High luminance light source: no
Anti-glare shield: no
Dimmable: no

PRODUCT PARAMETERS:

Colour: amber
Compatible with a dimmer: no
Height [mm]: 140
Diameter [mm]: 95
Mercury content: no
Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Lamp rated current [mA]: 38
Rated power [W]: 4
Total rated luminous flux [lm]: 250
Rated beam angle [°]: 320
Lampshade material: glass
Light source: G95
Diode type: LED FILAMENT
Colour temperature: super warm
Cap: E27
Rated lamp-service life [h]: 15000
Number of on/off cycles: ≥20000
Light source shape: globe

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Energy consumption in on-mode of the light source (kWh/1000h): 4
Useful luminous flux of the light source Φuse [lm]: 250
Useful luminous flux of the light source Φuse [lm]: in

Ø95

140

EN

Kanlux
ul. Objazdowa 1-3, 41-922 Radzionków, Poland

33518   XLED G95 4W-SW

LED light source

sphere (360°)
Correlated colour temperature [K]: 1800
Colour consistency in McAdam ellipses: ≤6
On-mode power of the light source Pon [W]: 4
Colour rendering index: 80
Claim of equivalent power [W]: 25

PARAMETERS FOR LED AND OLED MAINS LIGHT SOURCES:

Flicker metric (Pst LM): ≤1,0
Stroboscopic effect metric (SVM): ≤0,4

LOGISTIC DATA:

Packaging method: 5
Number of units in the secondary packaging: 5
Number of units in the packaging: 40
Net unit weight [g]: 52
Grammage [g]: 135
Length of a unit pack [cm]: 10
Width of a unit pack [cm]: 10
Height of a unit pack [cm]: 16
Weight of a cardboard box [kg]: 5.4
Width of a cardboard box [cm]: 44
Height of a cardboard box [cm]: 35
Length of a cardboard box [cm] : 53
Volume of a cardboard box [m³]: 0.08162

KANLUX S.A. (kat 33518) XLED G95 4W-SW / **LDC (Polar)**

Luminaire: KANLUX S.A. (kat 33518) XLED G95 4W-SW
Lamps: 1 x XLED G95 4W-SW

cd/klm   η = 100%
—— C0 - C180   —— C90 - C270