



by **Kanlux**


ul. Objazdowa 1-3, 41-922 Radzionków, Poland



33613 LOGI 02-1230-142 cm

Socket Outlet Earthed - With Protection Cover - FireProof Plastic

5905339336132



A grounded single socket outlet (Schuko) allows you to power an electrical circuit with a maximum load of 16A. In addition, the socket outlet has a hinged lid, thanks to which it maintains the IP rating of IP 44 and may be installed in areas with splash water (bathrooms).

PRODUCT PARAMETERS:

Colour: black matt

Place of assembly: Recessed mount in the wall

Width [mm]: 71

Height [mm]: 71

Diameter of an installation box: 60

Installation depth: 25

Number of sockets: 1

Rated voltage [V]: 250 AC

Rated current [A]: 16

Class of protection against electric shock: I

Material of contacts: CuZn70

Earthing type: type F

Terminal type: Screw terminal

Plastic: ABS

IP class: 44

LOGISTIC DATA:

Packaging method: 10

Number of units in the secondary packaging: 10

Number of units in the packaging: 120

Net unit weight [g]: 76

Grammage [g]: 89.75

Length of a unit pack [cm]: 9

Width of a unit pack [cm]: 5

Height of a unit pack [cm]: 14

Weight of a cardboard box [kg]: 10.77

Width of a cardboard box [cm]: 26.5

Height of a cardboard box [cm]: 32



by **Kanlux**

ul. Objazdowa 1-3, 41-922 Radzionków, Poland

33613 LOGI 02-1230-142 cm

Socket Outlet Earthed - With Protection Cover - FireProof Plastic

Length of a cardboard box [cm] : 44

Volume of a cardboard box [m³]: 0.037312