


## 33833 ITECH S1 302MATW

Emergency lighting LED

5902052541010



Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

### PRODUCT PARAMETERS:

**Colour:** white  
**Height [mm]:** 66.5  
**Diameter [mm]:** 170  
**Integrated LED light source:** yes  
**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Maximum power [W]:** 2  
**Class of protection against electric shock:** II  
**Diode type:** LED SMD  
**Luminous flux [lm]:** 245  
**Luminous flux [lm] (emergency-lighting module):** 245  
**Colour temperature:** cold white  
**Battery (type):** LiFePO4/C  
**Battery (parameters):** 6.4V  
**Operating mode:** emergency and network  
**Application:** anti-panic lighting  
**Fail-safe working time [h]:** 3  
**Automatic test:** yes  
**Enclosure material:** plastic  
**IP class:** 65

### PARAMETERS FOR LED AND OLED LIGHT SOURCES:

**Correlated colour temperature [K]:** 5000

### LOGISTIC DATA:

**Packaging method:** 1  
**Number of units in the secondary packaging:** 1  
**Number of units in the packaging:** 1

### ACCESSORIES:

**33830** UCHW PODT OS S2 S3 IT