


33860 ONTEC R M5 105 M STW

Emergency lighting LED

5902052520732



Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

PRODUCT PARAMETERS:

Colour: white

Place of assembly: wall mounted, ceiling mounted

Integrated LED light source: yes

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Rated power (LED) [W]: 4.5

Class of protection against electric shock: II

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 615

Luminous flux [lm] (emergency-lighting module): 615

Colour temperature: cold white

Battery (type): LiFEPO4/C

Battery (parameters): 6.4V

Operating mode: emergency and network

Application: anti-panic lighting

Fail-safe working time [h]: 1

Standard test: yes

Enclosure material: plastic

Connection type: Self-clamping block

IP class: 20

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Correlated colour temperature [K]: 5000

LOGISTIC DATA:

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 238

Grammage [g]: 282

Length of a unit pack [cm]: 13.5

Width of a unit pack [cm]: 4

Height of a unit pack [cm]: 13.5

Weight of a cardboard box [kg]: 0.282

Width of a cardboard box [cm]: 4

Height of a cardboard box [cm]: 13.5

Length of a cardboard box [cm]: 13.5

Volume of a cardboard box [m³]: 0.000729

33860 ONTEC R M5 105 M STW

Emergency lighting LED

ACCESSORIES:**33831 ZEST PODT OR00 W**