


33886 IQ-LED FL-20W-NW-SE

LED floodlight

**LED module:** I-FL-A71-04-A-V2.0**Luminous flux [lm]:** 2300**Colour temperature:** white**Service life [h]:** 50000**Number of on/off cycles:** ≥25000**Lighting angle [°]:** 100**Ambient temperature range to which the product can be exposed:** -30÷50**Enclosure material:** Metal**Sensor type:** PIR**Connection type:** Free cable ends**Wire type:** H05RN-F**Wire length [m]:** 0.3**Wire diameter [mm²]:** 1**Sensor-operation time [second-minute]:** 10-7**Lamp-heating time [s]:** ≤1**Lamp-ignition time [s]:** ≤0,5**sensor working angle [°]:** 120**Illumination-level setpoint by which the sensor detects movement [lx]:** 10-2000**The fixture is movable vertically [°]:** 180**IP class:** 44**Sensor range[m]:** max 8**Additional information:** Containing product (CP)**Mercury content:** no**PARAMETERS FOR LED AND OLED LIGHT SOURCES:****Energy consumption in on-mode of the light source (kWh/1000h):** 20**Energy efficiency class:** E**Useful luminous flux of the light source Φuse [lm]:** 2600**Useful luminous flux of the light source Φuse [lm]:** in sphere (360°)**Correlated colour temperature [K]:** 4000**Colour consistency in McAdam ellipses:** ≤6**On-mode power of the light source Pon [W]:** 20**Height of the light source [mm]:** 76**Width of the light source [mm]:** 60**Depth of the light source [mm]:** 16**Colour rendering index:** 80

**Kanlux**

ul. Objazdowa 1-3, 41-922 Radzionków, Poland

33886 IQ-LED FL-20W-NW-SE

LED floodlight

Chromaticity coordinates (x): 0,38
Chromaticity coordinates (y): 0,38
Claim of equivalent power [W]: 157
R9 colour rendering index value : >=0
Survival factor: 0,9
The lumen maintenance factor: 0,96

PARAMETERS FOR LED AND OLED MAINS LIGHT SOURCES:

Displacement factor (cos φ1): 0,9
LED light source replaces a fluorescent light source without integrated ballast of a particular wattage: Not applicable
Flicker metric (Pst LM): 1,0
Stroboscopic effect metric (SVM): 0,4

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 20
Number of units in the secondary packaging : 1
Number of units in the packaging : 20
Net unit weight [g]: 356
Grammage [g]: 446
Gross unit weight [g]: 424
Length of a unit pack [cm]: 14
Width of a unit pack [cm]: 6
Height of a unit pack [cm]: 17
Weight of a cardboard box [kg]: 8.92
Width of a cardboard box [cm]: 30
Height of a cardboard box [cm]: 19.5
Length of a cardboard box [cm] : 61
Volume of a cardboard box [m³]: 0.035685

ADDITIONAL INFORMATION:



- 5 years Warranty under the terms of the warranty statement, available on our website
-

**Kanlux**

ul. Objazdowa 1-3, 41-922 Radzionków, Poland

33886 IQ-LED FL-20W-NW-SE

LED floodlight

**KANLUX S.A. (kat 33886) IQ-LED FL-20W-NW-SE / LDC (Polar)**Luminaire: KANLUX S.A. (kat 33886) IQ-LED FL-20W-NW-SE
Lamps: 1 x IQ-LED FL-20W-NW**ACCESSORIES****33889**

IQ-LED FL QC I 3x1MM2



Hermetic quick connector for easy, quick and safe connection of the connecting cable and the floodlight, IQ-LED FL QC I 3x1MM2 (33889)