


33893 MEBA LED 40W IP54 NW

Linear LED luminaire

5905339338938



Kanlux MEBA LED IP54 is a series of surface-mounted luminaires that complements the popular family of Kanlux MEBA luminaires. We can choose from models with a length of 600mm and 1200mm. Kanlux MEBA LED IP54 means high luminous efficiency, durability of 50,000 hours and a 5-year warranty. An additional advantage of these luminaires is the IP54 level and two cable entries that allow for pass-through connection. The quick connector makes it easier to install the luminaire, and the lampshade and sides of the luminaire are made of polycarbonate and the body is made of steel sheet. These are other advantages of these luminaires.

PRODUCT PARAMETERS:

Colour: white**Place of assembly:** ceiling mounted**Place of application:** Indoors and outdoors**Minimum distance from the illuminated object:** 0,5m**Compatible with a dimmer:** no**Length [mm]:** 1213**Width [mm]:** 152**Height [mm]:** 57**Integrated LED light source:** yes**Rated voltage [V]:** 220-240 AC**Rated frequency [Hz]:** 50**Maximum power [W]:** 40**Class of protection against electric shock:** I**Lampshade material:** PC**Diode type:** LED SMD**Luminous flux [lm]:** 5200**Colour temperature:** white**Service life [h]:** 50000**Number of on/off cycles:** ≥25000**Lighting angle [°]:** 120**Ambient temperature range to which the product can be exposed:** -20+40**Enclosure material:** steel**Connection type:** Self-clamping block**Range of sections of wires used [mm²]:** 0,75-2**IP class:** 54**Additional information:** Possibility of replacing the LED light source only by qualified personnel (only by the manufacturer service)

33893 MEBA LED 40W IP54 NW

Linear LED luminaire



Additional information: Possibility of replacing the control equipment only by qualified personnel (only by the manufacturer service)

Additional information: Containing product (CP)

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Energy efficiency class: C

Useful luminous flux of the light source Φ_{use} [lm]: 2x 3380

Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses : 6

Colour rendering index: 80

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 6

Number of units in the secondary packaging : 1

Number of units in the packaging : 6

Net unit weight [g]: 1446

Grammage [g]: 1758.33

Length of a unit pack [cm]: 122

Width of a unit pack [cm]: 15.5

Height of a unit pack [cm]: 6.5

Weight of a cardboard box [kg]: 10.54998

Width of a cardboard box [cm]: 20

Height of a cardboard box [cm]: 33

Length of a cardboard box [cm] : 125

Volume of a cardboard box [m³]: 0.0825

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

