



**34000 AL-ML-NW-MPR-S-NT**


Linear LED luminaire

5905339340009

**PRODUCT PARAMETERS:****Colour:** silver**Place of assembly:** ceiling mounted**Place of application:** Indoors**Minimum distance from the illuminated object :** 0,5m**Compatible with a dimmer:** no**Fixture lighting direction:** down**Length [mm]:** 1140**Width [mm]:** 60**Height [mm]:** 69**Integrated LED light source:** yes**Version for connection in line [initial element] LF :** 34532**Version for connection in line [central element] LM :** 34676**Version for connection in line [final element] LL :** 34820**Rated voltage [V]:** 220-240 AC**Rated frequency [Hz]:** 50**Maximum power [W]:** 25**Class of protection against electric shock :** I**Lampshade material:** plastic**Diode type:** LED SMD**Luminous flux [lm]:** 3000**Colour temperature:** white**Service life [h]:** 50000**Luminous-flux-retention factor at the end of rated service life :**  
L90B10**Number of on/off cycles:** ≥30000**Lighting angle [°]:** X75/Y90**Ambient temperature range to which the product can be exposed:** 5÷25**Shade type:** microprismatic**Enclosure material:** aluminum alloy**Connection type:** Self-clamping block**Range of sections of wires used [mm²]:** 1,5÷2,5**Lamp-heating time [s]:** ≤1**Lamp-ignition time [s]:** ≤0,5**IP class:** 20**PARAMETERS FOR LED AND OLED LIGHT SOURCES:****Correlated colour temperature [K]:** 4000**Colour consistency in McAdam ellipses :** ≤3**Colour rendering index:** 80

## 34000 AL-ML-NW-MPR-S-NT

### Linear LED luminaire



#### LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 2100

Grammage [g]: 2450

Length of a unit pack [cm]: 136

Width of a unit pack [cm]: 11

Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 2.45

Width of a cardboard box [cm]: 11

Height of a cardboard box [cm]: 7

Length of a cardboard box [cm]: 136


Volume of a cardboard box [m³]: 0.010472

#### ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

KANLUX S.A. (kat 34000) AL-ML-NW-MPR-S-NT / LDC (Polar)

Luminaire: KANLUX S.A. (kat 34000) AL-ML-NW-MPR-S-NT  
Lamps: 1 x AL-ML-NW-MPR



## 34000 AL-ML-NW-MPR-S-NT

Linear LED luminaire

### ACCESSORIES

|                                                                                     |                      |                                                                                 |
|-------------------------------------------------------------------------------------|----------------------|---------------------------------------------------------------------------------|
| <b>32540</b>                                                                        | ALIN CORD 1F-W       | Power supply terminal for ALIN luminaires and tracks, 1-phase, white, 150 cm    |
|    |                      |                                                                                 |
| <b>32541</b>                                                                        | ALIN CORD 1F-B       | Power supply terminal for ALIN luminaires and tracks, 1-phase, black, 150 cm    |
|    |                      |                                                                                 |
| <b>32542</b>                                                                        | ALIN CORD 1F-SR      | Power supply terminal for ALIN luminaires and tracks, 1-phase, silver 150 cm    |
|   |                      |                                                                                 |
| <b>07871</b>                                                                        | ROPE-NT 150 SINGLE   | ROPE-NT 150 SINGLE steel rope (single) for suspending fittings, 2 pcs. in a set |
|  |                      |                                                                                 |
| <b>29557</b>                                                                        | ALIN NT GRIP         | Wall bracket for the ALIN luminaire, 2 pcs included                             |
|  |                      |                                                                                 |
| <b>25979</b>                                                                        | KLOSZ MPR AL 23W/33W | MPR shade for fitting ALIN, MPR SHADE AL 23W/33W, (25979)                       |
|  |                      |                                                                                 |