



34069 AL-MM-WW-MAT-B-PT

Linear LED luminaire

5905339340696



PRODUCT PARAMETERS:

Colour: black

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object : 0,5m

Compatible with a dimmer: no

Fixture lighting direction: down

Length [mm]: 1150

Width [mm]: 83

Height [mm]: 65

Integrated LED light source: yes

Version for connection in line [initial element] LF : 34594 (PT)

Version for connection in line [central element] LM : 34738 (PT)

Version for connection in line [final element] LL : 34882 (PT)

Explanation of markings and signs used : (PT) - do wbudowania w sufit

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 29

Class of protection against electric shock : I

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 3450

Colour temperature: Warm white

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life : L90B10

Number of on/off cycles: ≥ 30000

Lighting angle [°]: X85/Y95

Ambient temperature range to which the product can be exposed: 5÷25

Shade type: matt

Enclosure material: steel

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 1,5÷2,5

Lamp-heating time [s]: ≤ 1

Lamp-ignition time [s]: $\leq 0,5$

IP class: 20

PARAMETERS FOR LED AND OLED LIGHT SOURCES:


Correlated colour temperature [K]: 3000

Colour consistency in McAdam ellipses: ≤ 3

Colour rendering index: 80

34069 AL-MM-WW-MAT-B-PT

Linear LED luminaire



LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 1464

Grammage [g]: 1800

Length of a unit pack [cm]: 136

Width of a unit pack [cm]: 11

Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 1.8

Width of a cardboard box [cm]: 11

Height of a cardboard box [cm]: 7

Length of a cardboard box [cm]: 136

Volume of a cardboard box [m³]: 0.010472

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

KANLUX S.A. (kat 34069) AL-MM-WW-MAT-B-PT / LDC (Polar)

Luminaire: KANLUX S.A. (kat 34069) AL-MM-WW-MAT-B-PT
Lamps: 1 x AL-MM-WW-MAT

