Kanlux

ul. Objazdowa 1-3, 41-922 Radzionków, Poland

34176 ALD-SL-NW-MAT-S-NT

Linear LED luminaire

5905339341761

LED techno logy

DALI system

PRODUCT PARAMETERS:

Colour: silver

Place of assembly: ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: DALI

Fixture lighting direction: down

Length [mm]: 580

Width [mm]: 60

Height [mm]: 69

Integrated LED light source: yes

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 10

Class of protection against electric shock: I

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 1300

Colour temperature: white

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life: L90B10

Number of on/off cycles: ≥30000

Lighting angle [°]: X85/Y95

Ambient temperature range to which the product can be exposed: 5÷25

Shade type: matt

Enclosure material: aluminum alloy

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 0,5÷2,5

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

IP class: 20

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: ≤3

Colour rendering index: 80

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1

Number of units in the secondary packaging: 1

573

65

58

Date of issue: 01.03.2023, 22:15
We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.

EN

Kanlux

ul. Objazdowa 1-3, 41-922 Radzionków, Poland

34176   ALD-SL-NW-MAT-S-NT

Linear LED luminaire

Number of units in the packaging : 1
Net unit weight [g] : 1300
Grammage [g] : 1377
Length of a unit pack [cm] : 75
Width of a unit pack [cm] : 11
Height of a unit pack [cm] : 7
Weight of a cardboard box [kg] : 1.377
Width of a cardboard box [cm] : 11
Height of a cardboard box [cm] : 7
Length of a cardboard box [cm] : 75
Volume of a cardboard box [m³] : 0.005775

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

EN

Kanlux

ul. Objazdowa 1-3, 41-922 Radzionków, Poland

34176   ALD-SL-NW-MAT-S-NT

Linear LED luminaire

ACCESSORIES

32543	ALIN CORD DALI 1F-W		Power supply terminal for ALIN luminaires and tracks, 1-phase, DALI, white, 150 cm
32544	ALIN CORD DALI 1F-B		Power supply terminal for ALIN luminaires and tracks, 1-phase, DALI, black, 150 cm
32545	ALIN CORD DALI 1F-SR		Power supply terminal for ALIN luminaires and tracks, 1-phase, DALI, silver, 150 cm
07871	ROPE-NT 150 SINGLE		ROPE-NT 150 SINGLE steel rope (single) for suspending fittings, 2 pcs. in a set
29557	ALIN NT GRIP		Wall bracket for the ALIN luminaire, 2 pcs included
27109	KLOSZ MPR AL 11W/17W		MPR shade for fitting ALIN, MPR SHADE AL 11W/17W, (27109)

EN