

34277 ALD-MH-NW-MPR-B-PT

Linear LED luminaire

5905339342775



PRODUCT PARAMETERS:

Colour: black

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: DALI

Fixture lighting direction: down

Length [mm]: 1150

Width [mm]: 83

Height [mm]: 65

Integrated LED light source: yes

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 40

Class of protection against electric shock: I

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 4650

Colour temperature: white

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life: L90B10

Number of on/off cycles: ≥ 30000

Lighting angle [°]: X75/Y90

Ambient temperature range to which the product can be exposed: 5÷25

Shade type: microprismatic

Enclosure material: steel

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 0,5÷2,5

Lamp-heating time [s]: ≤ 1

Lamp-ignition time [s]: $\leq 0,5$

IP class: 20

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: ≤ 3

Colour rendering index: 80

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1

Number of units in the secondary packaging: 1

34277 ALD-MH-NW-MPR-B-PT

Linear LED luminaire

Number of units in the packaging: 1**Net unit weight [g]:** 1630**Grammage [g]:** 1960**Length of a unit pack [cm]:** 136**Width of a unit pack [cm]:** 11**Height of a unit pack [cm]:** 7**Weight of a cardboard box [kg]:** 1.96**Width of a cardboard box [cm]:** 11**Height of a cardboard box [cm]:** 7**Length of a cardboard box [cm] :** 136**Volume of a cardboard box [m³]:** 0.010472**ADDITIONAL INFORMATION:**

- 5 years Warranty under the terms of the warranty statement, available on our website