



34404 AL-SH-NW-MAT-B-NT-SE

Linear LED luminaire

5905339344045

**PRODUCT PARAMETERS:****Colour:** black**Place of assembly:** ceiling mounted**Place of application:** Indoors**Micro-interval between relay contacts:** yes**Minimum distance from the illuminated object:** 0,5m**Compatible with a dimmer:** no**Wykrywanie ruchu:** yes**Fixture lighting direction:** down**Length [mm]:** 680**Width [mm]:** 60**Height [mm]:** 69**Sensitivity regulation:** yes**Integrated LED light source:** yes**Rated voltage [V]:** 220-240 AC**Rated frequency [Hz]:** 50**Maximum power [W]:** 20**Class of protection against electric shock:** I**Lampshade material:** plastic**Diode type:** LED SMD**Luminous flux [lm]:** 2550**Colour temperature:** white**Service life [h]:** 50000**Luminous-flux-retention factor at the end of rated service life:****L90B10****Number of on/off cycles:** ≥30000**Lighting angle [°]:** X85/Y95**Ambient temperature range to which the product can be exposed:** 5÷25**Shade type:** matt**Enclosure material:** aluminum alloy**Sensor type:** microwave**Connection type:** Self-clamping block**Range of sections of wires used [mm²]:** 1,5÷2,5**Sensor-operation time [second-minute]:** 5-15**Lamp-heating time [s]:** ≤1**Lamp-ignition time [s]:** ≤0,5**Sensor-operation frequency [MHz]:** 5800**sensor working angle [°]:** 360**Illumination-level setpoint by which the sensor detects movement [lx]:** OFF/50/10/2**IP class:** 20**Sensor range[m]:** max 5

34404 AL-SH-NW-MAT-B-NT-SE

Linear LED luminaire

**Mercury content:** no**PARAMETERS FOR LED AND OLED LIGHT SOURCES:****Correlated colour temperature [K]:** 4000**Colour consistency in McAdam ellipses :** ≤3**Colour rendering index:** 80**LOGISTIC DATA:****Unit of measurement:** unit**Packaging method:** 1**Number of units in the secondary packaging :** 1**Number of units in the packaging :** 1**Net unit weight [g]:** 1318**Grammage [g]:** 1500**Length of a unit pack [cm]:** 75**Width of a unit pack [cm]:** 11**Height of a unit pack [cm]:** 7**Weight of a cardboard box [kg]:** 1.5**Width of a cardboard box [cm]:** 11**Height of a cardboard box [cm]:** 7**Length of a cardboard box [cm] :** 75**Volume of a cardboard box [m³]:** 0.005775**ADDITIONAL INFORMATION:**

- 5 years Warranty under the terms of the warranty statement, available on our website

34404 AL-SH-NW-MAT-B-NT-SE

Linear LED luminaire

ACCESSORIES**32540**

ALIN CORD 1F-W



Power supply terminal for ALIN luminaires and tracks, 1-phase, white, 150 cm

32541

ALIN CORD 1F-B



Power supply terminal for ALIN luminaires and tracks, 1-phase, black, 150 cm

32542

ALIN CORD 1F-SR



Power supply terminal for ALIN luminaires and tracks, 1-phase, silver 150 cm

07871

ROPE-NT 150 SINGLE



ROPE-NT 150 SINGLE steel rope (single) for suspending fittings, 2 pcs. in a set

29557

ALIN NT GRIP



Wall bracket for the ALIN luminaire, 2 pcs included