


35276 XLED G45 E14 6W-WW

LED light source

5905339352767



Kanlux XLED combines the best features of traditional bulbs and modern LED light sources. Therefore, we talk about it as the first real LED bulb. A glass bulb in the shape of a traditional “ball” and LED diodes placed in such a way so that light can part in all directions. You choose from sources with E27 and E14 light bulb bases.

TYPE OF LIGHT SOURCE:**Lighting technology used:** LED**Non-directional or directional light source :** NDLS**Mains or non-mains light source :** MLS**Connected light source (CLS):** no**Colour-tuneable light source:** no**High luminance light source:** no**Anti-glare shield:** no**Dimmable:** no**PRODUCT PARAMETERS:****Colour:** transparent**Compatible with a dimmer:** no**Width [mm]:** 45**Height [mm]:** 80**Depth [mm]:** 45**Diameter [mm]:** 45**Rated voltage [V]:** 220-240 AC**Rated frequency [Hz]:** 50**Lamp rated current [mA]:** 38**Rated power [W]:** 6**Total rated luminous flux [lm]:** 806**Rated beam angle [°]:** 320**Lampshade material:** glass**Light source:** G45**Diode type:** LED FILAMENT**Colour temperature:** Warm white**Cap (Light source):** E14**Rated lamp-service life [h]:** 15000**Number of on/off cycles:** ≥25000**Light source shape:** golf**Additional information:** Light source (LS)**Mercury content:** no**Luminous efficiency of the lamp [lm/W]:** 134

35276 XLED G45 E14 6W-WW

LED light source



PARAMETERS FOR DIRECTIONAL LIGHT SOURCES:

Beam angle [°]: 320

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Energy consumption in on-mode of the light source

(kWh/1000h): 6

Energy efficiency class: E

Useful luminous flux of the light source Φ_{use} [lm]: 806

Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)

Correlated colour temperature [K]: 2700

Colour consistency in McAdam ellipses: 6

On-mode power of the light source P_{on} [W]: 6

Height of the light source [mm]: 80

Width of the light source [mm]: 45

Depth of the light source [mm]: 45

Colour rendering index: 80

Chromaticity coordinates (x): 0.458

Chromaticity coordinates (y): 0.41

Claim of equivalent power [W]: 60

R9 colour rendering index value: 20

Survival factor: 0,9

The lumen maintenance factor: 0,96

PARAMETERS FOR LED AND OLED MAINS LIGHT SOURCES:

Displacement factor ($\cos \phi_1$): 0.5

LED light source replaces a fluorescent light source without integrated ballast of a particular wattage: Not applicable

Flicker metric ($P_{\text{st LM}}$): 1,0

Stroboscopic effect metric (SVM): 0.4

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 10

Number of units in the secondary packaging: 10

Number of units in the packaging: 100

Net unit weight [g]: 14

Grammage [g]: 33

Gross unit weight [g]: 29

Length of a unit pack [cm]: 5

Width of a unit pack [cm]: 5

Height of a unit pack [cm]: 9.5

Weight of a cardboard box [kg]: 3.3

Width of a cardboard box [cm]: 28

35276 XLED G45 E14 6W-WW

LED light source

Height of a cardboard box [cm]: 22

Length of a cardboard box [cm] : 53

Volume of a cardboard box [m³] : 0.032648

