



35678 TIBERI PRO NT30W-940W

Downlight fitting

5905339356789



Kanlux TIBERI PRO NT is a family of surface-mounted downlights. They are available in two wattages (20W and 30W) and two colors (white and black) while keeping the same size. The Kanlux TIBERI PRO luminaire is primarily characterized by high tightness (IP54) and high color rendering index (Ra> 90), but also easy installation on the ceiling using a bracket. The Kanlux TIBERI PRO NT luminaire is a high quality component confirmed by a 5-year warranty.

PRODUCT PARAMETERS:**Colour:** white**Place of assembly:** ceiling mounted**Place of application:** Indoors**Minimum distance from the illuminated object:** 0,5m**Compatible with a dimmer:** no**Height [mm]:** 113**Diameter [mm]:** 170**Rated voltage [V]:** 220-240 AC**Rated frequency [Hz]:** 50**Maximum power [W]:** 30**Class of protection against electric shock:** I**Lampshade material:** plastic**Diode type:** LED SMD**Luminous flux [lm]:** 3000**Colour temperature:** white**Service life [h]:** 50000**Number of on/off cycles:** ≥30000**Lighting angle [°]:** 115**Enclosure material:** aluminum alloy**Connection type:** Free cable ends**Wire length [m]:** 0.18**Wire diameter [mm²]:** 0,75**Lamp-heating time [s]:** ≤1**Lamp-ignition time [s]:** ≤0,5**IP class:** 54**PARAMETERS FOR LED AND OLED LIGHT SOURCES:****Correlated colour temperature [K]:** 4000**Colour consistency in McAdam ellipses:** ≤6**Colour rendering index:** 90

35678 TIBERI PRO NT30W-940W

Downlight fitting

LOGISTIC DATA:**Packaging method:** 12**Number of units in the secondary packaging:** 1**Number of units in the packaging:** 12**Net unit weight [g]:** 1162**Grammage [g]:** 1323.33**Length of a unit pack [cm]:** 17.5**Width of a unit pack [cm]:** 17.5**Height of a unit pack [cm]:** 12.5**Weight of a cardboard box [kg]:** 15.87996**Width of a cardboard box [cm]:** 37**Height of a cardboard box [cm]:** 28**Length of a cardboard box [cm]:** 54.5**Volume of a cardboard box [m³]:** 0.056462**ADDITIONAL INFORMATION:**

- 5 years Warranty under the terms of the warranty statement, available on our website