


## 35947 OS-M5D-WW-RST-B-N3

Surface-mounted LED office fixture

5905339359476



### PRODUCT PARAMETERS:

**Colour:** black

**Place of assembly:** ceiling mounted

**Place of application:** Indoors

**Minimum distance from the illuminated object :** 0,5m

**Compatible with a dimmer:** no

**The product is not suitable to be covered with a heat-insulating material:** yes

**Length [mm]:** 1200

**Width [mm]:** 300

**Height [mm]:** 35

**Integrated LED light source :** yes

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** 39W

**Class of protection against electric shock :** I

**Lampshade material:** plastic

**Diode type:** LED SMD

**Luminous flux of the light fitting [lm]:** 4800

**Colour temperature:** Warm white

**Service life [h]:** 50000

**Luminous-flux-retention factor at the end of rated service life :** L90B10

**Number of on/off cycles:**  $\geq 30000$

**Lighting angle [°]:** 50

**Ambient temperature range to which the product can be exposed:** 5÷25

**Shade type:** louvre

**Enclosure material:** Metal

**Connection type:** Self-clamping block

**Range of sections of wires used [mm²]:** 1,5÷2,5

**Lamp-heating time [s]:**  $\leq 1$

**Lamp-ignition time [s]:**  $\leq 0,5$

**Rodzaj soczewki [°]:** 50

**IP class:** 20

**Additional information:** The LED light source can only be replaced by qualified personnel (Kanlux service only)

**Additional information:** Any control panel or control equipment can only be replaced by qualified personnel (Kanlux service only)


**Additional information:** Containing product (CP)

### PARAMETERS FOR LED AND OLED LIGHT SOURCES:

**Correlated colour temperature [K]:** 3000

## 35947 OS-M5D-WW-RST-B-N3

Surface-mounted LED office fixture



**Colour consistency in McAdam ellipses :  $\leq 3$**

**Colour rendering index : 80**

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 1

**Number of units in the secondary packaging :** 1

**Number of units in the packaging :** 1

### ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

KANLUX S.A. (kat 35947) OS-M5D-WW-RST-B-N3 / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 35947) OS-M5D-WW-RST-B-N3  
Lampy: 4 x OS-M5D-WW-RST

