


35963 OS-M5D-NW-RST-B-N3

Surface-mounted LED office fixture

5905339359636



PRODUCT PARAMETERS:

Colour: black

Place of assembly: ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating material: yes

Length [mm]: 1200

Width [mm]: 300

Height [mm]: 35

Integrated LED light source: yes

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 39W

Class of protection against electric shock: I

Lampshade material: plastic

Diode type: LED SMD

Luminous flux of the light fitting [lm]: 4800

Colour temperature: white

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life: L90B10

Number of on/off cycles: ≥ 30000

Lighting angle [°]: 50

Ambient temperature range to which the product can be exposed: 5÷25

Shade type: louvre

Enclosure material: Metal

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 1,5÷2,5

Lamp-heating time [s]: ≤ 1

Lamp-ignition time [s]: $\leq 0,5$

Rodzaj soczewki [°]: 50

IP class: 20

Additional information: The LED light source can only be replaced by qualified personnel (Kanlux service only)

Additional information: Any control panel or control equipment can only be replaced by qualified personnel (Kanlux service only)

Additional information: Containing product (CP)

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Correlated colour temperature [K]: 4000

35963 OS-M5D-NW-RST-B-N3

Surface-mounted LED office fixture



Colour consistency in McAdam ellipses : ≤ 3

Colour rendering index: 80

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1

Number of units in the secondary packaging : 1

Number of units in the packaging: 1

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

KANLUX S.A. (kat 35963) OS-M5D-NW-RST-B-N3 / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 35963) OS-M5D-NW-RST-B-N3
Lampy: 4 x OS-M5D-NW-RST

