


## 35999 OS-H8D-NW-RST-B-N3

Surface-mounted LED office fixture

5905339359995



### PRODUCT PARAMETERS:

- Colour:** black  
**Place of assembly:** ceiling mounted  
**Place of application:** Indoors  
**Minimum distance from the illuminated object:** 0,5m  
**Compatible with a dimmer:** no  
**The product is not suitable to be covered with a heat-insulating material:** yes  
**Length [mm]:** 1200  
**Width [mm]:** 300  
**Height [mm]:** 35  
**Integrated LED light source:** yes  
**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Maximum power [W]:** 49W  
**Class of protection against electric shock:** I  
**Lampshade material:** plastic  
**Diode type:** LED SMD  
**Luminous flux of the light fitting [lm]:** 5600  
**Colour temperature:** white  
**Service life [h]:** 50000  
**Luminous-flux-retention factor at the end of rated service life:** L90B10  
**Number of on/off cycles:**  $\geq 30000$   
**Lighting angle [°]:** 80  
**Ambient temperature range to which the product can be exposed:** 5÷25  
**Shade type:** louvre  
**Enclosure material:** Metal  
**Connection type:** Self-clamping block  
**Range of sections of wires used [mm<sup>2</sup>]:** 1,5÷2,5  
**Lamp-heating time [s]:**  $\leq 1$   
**Lamp-ignition time [s]:**  $\leq 0,5$   
**Rodzaj soczewki [°]:** 80  
**IP class:** 20  
**Additional information:** The LED light source can only be replaced by qualified personnel (Kanlux service only)  
**Additional information:** Any control panel or control equipment can only be replaced by qualified personnel (Kanlux service only)  
**Additional information:** Containing product (CP)

### PARAMETERS FOR LED AND OLED LIGHT SOURCES:

**Correlated colour temperature [K]:** 4000

Date of issue: 10.07.2024, 12:33

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

## 35999 OS-H8D-NW-RST-B-N3

Surface-mounted LED office fixture



Colour consistency in McAdam ellipses :  $\leq 3$

Colour rendering index: 80

### LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1

Number of units in the secondary packaging : 1

Number of units in the packaging: 1

### ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

KANLUX S.A. (kat 35999) OS-H8D-NW-RST-B-N3 / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 35999) OS-H8D-NW-RST-B-N3  
Lampy: 4 x OS-H8D-NW-RST

