

36290 KMCCB-F-125A

MCCB molded case circuit breaker

5905339362902



PRODUCT PARAMETERS:

Rated voltage [V]: 230/400 AC

Rated frequency [Hz]: 50

Rated current [A]: 125

Utilisation category: A

Place of assembly: mounting plate

IP class: 20

Znamionowa graniczna zwarciova zdolność łączeniowa Icu :
25kA (380/415V AC); 36kA (220/230V AC)

Prąd znamionowy wyłączalny zwarciovy roboczy Ics : 18kA
(380/415V AC); 25kA (220/230V AC)

Length [mm]: 75

Width [mm]: 82

Height [mm]: 133

Connection type: Terminal block

Control type: mechaniczne

Rated breaking voltage Ue [V]: 380/415; 220/230

Rated insulation voltage UI [V]: 800

Rated impulse withstand voltage Uimp [V]: 8000

Number of poles: 3

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 20

Number of units in the secondary packaging : 1

Number of units in the packaging : 20

Net unit weight [g]: 868

Grammage [g]: 935

Gross unit weight [g]: 910

Length of a unit pack [cm]: 14

Width of a unit pack [cm]: 8.5

Height of a unit pack [cm]: 9

Weight of a cardboard box [kg]: 18.7

Width of a cardboard box [cm]: 31


Height of a cardboard box [cm]: 21

Length of a cardboard box [cm]: 45

Volume of a cardboard box [m³]: 0.029295

36290 KMCCB-F-125A

MCCB molded case circuit breaker



ACCESSORIES

36294



KMCCB-F-125A/AL/L styk alarmowy

36293



KMCCB-F-125A/AX/L styk pomocniczy

36303



KMCCB-F-125A/RL/R wyzwalacz wzrostowy

36296



KMCCB-F-125A/UV wyzwalacz podnapięciowy

36298



KMCCB-F-250A/AL/L styk alarmowy

36297




KMCCB-F-250A/AX/L styk pomocniczy

36290 KMCCB-F-125A

MCCB molded case circuit breaker

125A, 160A: 6Nm
250A: 12Nm
400A: 20Nm



Unit:mm

No.	Frame size	Terminal block Width b	Terminal block Inner hole d	Terminal block Hole margin a
1	125	16	Ø 9	7
2	160	17	Ø 9	7
3	250	22	Ø 9	9
4	400	30	Ø 11	12.4



3P:
125A: 6x M8x16mm
160A, 250A: 6x M8x20mm
400A: 6x M10x30mm

4P:
125A: 8x M8x16mm
160A, 250A: 8x M8x20mm
400A: 8x M10x30mm



36306

KMCCB-F-250A/RL/R wyzwalacz wzrostowy



36300

KMCCB-F-250A/UV wyzwalacz podnapięciowy

