

37175 BLINGO U34W 4080 120N

Recessed-mounted LED panel

5905339371751



Kanlux BLINGO LED v2 are backlight panels. They are equipped with a junction box with a quick connector, which allows for pass-through connection of panels and speeds up their installation. In the new models of the well-known Kanlux BLINGO LED v2 panels, we have introduced an integrated power supply, thanks to which we can place them in an appropriate Kanlux ADTR frame and perform surface-mounting of the panels. BLINGO LED v2 panels have a grooved frame and higher luminous efficiency than their previous versions (Kanlux BLINGO LED).

PRODUCT PARAMETERS:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 34

Power factor: 0.92

Luminous flux of the light fitting [lm]: 4080

Luminous efficiency of the lamp [lm/W]: 120

Skuteczność świetlna [lm/W]: 120

Lighting angle [°]: 90

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: 6

Colour temperature: white

Colour rendering index: 80

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life: L70B50

Number of on/off cycles: ≥50000

Diode type: LED SMD

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating material: yes

Feeder included: yes


Length [mm]: 1195

Width [mm]: 295

Height [mm]: 27

37175 BLINGO U34W 4080 120N

Recessed-mounted LED panel



		BLINGO 24W 4320 60NW	BLINGO U24W 4080 60NW	BLINGO 34W 4080 60NW	BLINGO 34W 3740 60WW	BLINGO 34W 4080 60CW	BLINGO U34W 4080 60NW	BLINGO 34W 4080 120NW
	INDEX	37178	37179	37171	37170	37172	37173	37174
SPN PANEL 120	37336							✓
SPN PANEL 60-62	37335	✓	✓	✓	✓	✓	✓	
CLIPS PANEL 120	37338							✓
CLIPS PANEL 60-62	37337	✓	✓	✓	✓	✓	✓	
ADTR 6060 B	27615	✓	✓	✓	✓	✓	✓	
ADTR 6060 SR	27610	✓	✓	✓	✓	✓	✓	
ADTR 6060 W	27613	✓	✓	✓	✓	✓	✓	
ADTR-S 6060 W	27616	✓	✓	✓	✓	✓	✓	
ADTR 12030 B	27614							✓
ADTR 12030 SR	27612							✓
ADTR 12030 W	27611							✓
ADTR-H 6060 B	29845	✓	✓	✓	✓	✓	✓	
ADTR-H 6060 SR	29844	✓	✓	✓	✓	✓	✓	
ADTR-H 6060 W	29843	✓	✓	✓	✓	✓	✓	
ADTR-S-H 6060 W	27617	✓	✓	✓	✓	✓	✓	
ADTR-H 76MM 6060 W	33398	✓	✓	✓	✓	✓	✓	
ADTR-H 12030 B	33391							✓
ADTR-H 12030 SR	33392							✓
ADTR-H 12030 W	33390							✓
ADTR-H 6262 W	33435							

Integrated LED light source : yes
Class of protection against electric shock : I
Lampshade material: plastic
Enclosure material: steel
Panel/frame material: steel
Ambient temperature range to which the product can be exposed: 5÷25
Shade type: microprismatic
Range of sections of wires used [mm²]: 1-2,5
IP class: 20
Kształt: rectangular
UGR: <19
Additional information: Possibility of replacing the LED light source only by qualified personnel (only by the manufacturer service)
Additional information: The control panel or control equipment can be replaced by the end user
Additional information: Containing product (CP)
Mercury content in the lamp [mg] : 0

PARAMETERS FOR LED AND OLED LIGHT SOURCES:
Energy efficiency class of the light source in the contains product (CP): D
Number of modules (LED light source): 1
Useful luminous flux of the light source Φ_{use} [lm] : 4980
Useful luminous flux of the light source Φ_{use} [lm] : in sphere (360°)
Survival factor: 0,9
The lumen maintenance factor: 0,96
Lighting technology used: LED
Non-directional or directional light source : NDLS
Mains or non-mains light source : NMLS
Connected light source (CLS): no
Colour-tuneable light source: no
High luminance light source: no
Anti-glare shield: no
Dimmable: no

LOGISTIC DATA:
Unit of measurement: unit
Packaging method: 5
Number of units in the secondary packaging : 1

37175 BLINGO U34W 4080 120N

Recessed-mounted LED panel

	INDEX	BLINGO 38W 4560 60NW	BLINGO 38W 4560 120NW	BLINGO TN38W 6060 NW	BLINGO TUN48W 6060 NW	BLINGO IPN38W 6060NW	BLINGO IP65 40W 60NW
SPN PANEL 120	37336		✓				
SPN PANEL 60-62	37335	✓		✓	✓	✓	✓
CLIPS PANEL 120	37338		✓				
CLIPS PANEL 60-62	37337	✓		✓	✓	✓	✓
ADTR 6060 B	27615	✓		✓	✓		
ADTR 6060 SR	27610	✓		✓	✓		
ADTR 6060 W	27613	✓		✓	✓		
ADTR-S 6060 W	27616	✓		✓	✓		
ADTR 12030 B	27614		✓				
ADTR 12030 SR	27612		✓				
ADTR 12030 W	27611		✓				
ADTR-H 6060 B	29845	✓		✓	✓	✓	✓
ADTR-H 6060 SR	29844	✓		✓	✓	✓	✓
ADTR-H 6060 W	29843	✓		✓	✓	✓	✓
ADTR-S-H 6060 W	27617	✓		✓	✓	✓	✓
ADTR-H 76MM 6060 W	33398	✓		✓	✓	✓	✓
ADTR-H 12030 B	33391		✓				
ADTR-H 12030 SR	33392		✓				
ADTR-H 12030 W	33390		✓				
ADTR-H 6262 W	33435						

Number of units in the packaging : 5

Net unit weight [g] : 1626

Grammage [g] : 2118

Length of a unit pack [cm] : 120.5

Width of a unit pack [cm] : 3

Height of a unit pack [cm] : 31

Weight of a cardboard box [kg] : 10.59

Width of a cardboard box [cm] : 19.5


Height of a cardboard box [cm] : 33.7

Length of a cardboard box [cm] : 122

Volume of a cardboard box [m³] : 0.080172

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website



KANLUX S.A. (kat 37175) BLINGO U34W 4080 120NW / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 37175) BLINGO U34W 4080 120NW
Lampy: 1 x BLINGO U34W 4080 120NW

