

## 37182 OS-M8D-WW-RX-W-P1

Oprawa LED podtynkowa

5905339371829



### PRODUCT PARAMETERS:

**Colour:** white

**Place of assembly:** Recessed mount in the ceiling

**Place of application:** Indoors

**Minimum distance from the illuminated object:** 0,5m

**Compatible with a dimmer:** no

**The product is not suitable to be covered with a heat-insulating material:** yes

**Length [mm]:** 595

**Width [mm]:** 595

**Height [mm]:** 41

**Integrated LED light source:** yes

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** 40

**Class of protection against electric shock:** I

**Lampshade material:** plastic

**Diode type:** LED SMD

**Luminous flux of the light fitting [lm]:** 5250

**Colour temperature:** Warm white

**Service life [h]:** 50000

**Luminous-flux-retention factor at the end of rated service life:** L90B10

**Number of on/off cycles:**  $\geq 30000$

**Lighting angle [°]:** 80

**Ambient temperature range to which the product can be exposed:** 5÷25

**Shade type:** louvre / white

**Enclosure material:** Metal

**Connection type:** Self-clamping block

**Range of sections of wires used [mm<sup>2</sup>]:** 1,5÷2,5

**Lamp-heating time [s]:**  $\leq 1$

**Lamp-ignition time [s]:**  $\leq 0,5$

**IP class:** 20

**Additional information:** Containing product (CP)

### PARAMETERS FOR LED AND OLED LIGHT SOURCES:

**Correlated colour temperature [K]:** 3000

**Colour consistency in McAdam ellipses:**  $\leq 3$


**Colour rendering index:** 80

### LOGISTIC DATA:

**Unit of measurement:** unit

## 37182 OS-M8D-WW-RX-W-P1

Oprawa LED podtynkowa



**Packaging method: 1**

**Number of units in the secondary packaging: 1**

**Number of units in the packaging: 1**

KANLUX S.A. (kat 37182) OS-M8D-WW-RX-W-P1 / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 37182) OS-M8D-WW-RX-W-P1  
Lampy: 4 x OS-M8D-WW

